0202142

https://www.phoenixcontact.com/us/products/0202142



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Insertion bridge, pitch: 8 mm, number of positions: 4, color: gray



## Commercial data

Item number	0202142
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BE19
Product key	BE1Z2X
Catalog page	Page 117 (C-1-2019)
GTIN	4046356750028
Weight per piece (including packing)	4.5 g
Weight per piece (excluding packing)	4.447 g
Customs tariff number	85366990
Country of origin	PL

0202142

https://www.phoenixcontact.com/us/products/0202142



### Technical data

#### Product properties

Product type	Insertion bridge
Number of positions	4
Pitch	8 mm

#### Dimensions

	Pitch	8 mm
--	-------	------

#### Material specifications

Color	gray
Material	Copper
Insulating material	PA

#### Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-60 °C 105 °C
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (storage/transport)	30 % 70 %

#### Mounting

Mounting type	Screw mounting

0202142

https://www.phoenixcontact.com/us/products/0202142



## Classifications

#### ECLASS

ECLASS-11.0	27141140
ECLASS-12.0	27141140
ECLASS-13.0	27250303

#### ETIM

	ETIM 9.0	EC000489
UNSPSC		
	UNSPSC 21.0	39121400

0202142 https://www.phoenixcontact.com/us/products/0202142 **PHŒNIX** CONTACT

# Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com