0203153

https://www.phoenixcontact.com/us/products/0203153



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Insertion bridge, pitch: 10 mm, number of positions: 2, color: gray



Commercial data

Item number	0203153
Packing unit	100 рс
Minimum order quantity	100 рс
Sales key	BE19
Product key	BE1Z2X
Catalog page	Page 493 (C-1-2019)
GTIN	4017918098308
Weight per piece (including packing)	3.031 g
Weight per piece (excluding packing)	2.745 g
Customs tariff number	85366990
Country of origin	PL

0203153

https://www.phoenixcontact.com/us/products/0203153



Technical data

Product properties

Product type	Insertion bridge
Number of positions	2
Pitch	10 mm

Dimensions

	Pitch	10 mm
--	-------	-------

Material specifications

Color	gray
Material	Cu
Flammability rating according to UL 94	V0
Insulating material	PVC

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-60 °C 105 °C
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (storage/transport)	30 % 70 %

Mounting

Mounting type	Screw mounting
Mounting type	Selew meaning

0203153

https://www.phoenixcontact.com/us/products/0203153



Classifications

ECLASS

ECLASS-11.0	27141140
ECLASS-12.0	27141140
ECLASS-13.0	27250303

ETIM

	ETIM 9.0	EC000489
UNSPSC		
	UNSPSC 21.0	39121400

0203153 https://www.phoenixcontact.com/us/products/0203153



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com