

# CT-TERMIBLOCK 10 DA - Screw termination block



0441711

<https://www.phoenixcontact.com/us/products/0441711>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Screw termination block with disconnect contacts for accommodating protective plugs CT and CTM. Use in MCR and telecommunications systems. Design: 10 double wires

## Your advantages

- Space-saving due to compact design
- Flexible fields of application with modular protective plug
- Maximum ease of maintenance, thanks to the 2-piece design

## Commercial data

Item number	0441711
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	CL03
Product key	CL321Z
Catalog page	Page 193 (C-4-2019)
GTIN	4017918002213
Weight per piece (including packing)	172 g
Weight per piece (excluding packing)	167.6 g
Customs tariff number	85369010
Country of origin	DE

# CT-TERMIBLOCK 10 DA - Screw termination block



0441711

<https://www.phoenixcontact.com/us/products/0441711>

## Technical data

### Product properties

Type	LSA-PLUS module
Product type	Screw termination block
Product family	COMTRAB
Wire pairs per module	10


### Insulation characteristics

Overvoltage category	III
Pollution degree	3

### Connection data

Connection method	Screw terminal blocks
Screw thread	M3
Tightening torque	0.5 Nm
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12

### Dimensions

Dimensional drawing	
Width	118 mm
Height	43 mm
Depth	40.9 mm

### Material specifications

Color	black (RAL 9005)
Flammability rating according to UL 94	V2
Insulating material group	I / 600
Contact material	Cu alloy
Contact surface material	Sn
Housing material	PA

### Mechanical properties

#### Mechanical data

Open side panel	No
-----------------	----

# CT-TERMIBLOCK 10 DA - Screw termination block



0441711

<https://www.phoenixcontact.com/us/products/0441711>

## Protective circuit

Maximum continuous voltage $U_C$	240 V AC
Operating effective current $I_C$ at $U_C$	5 A

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Altitude	2000 m

## Standards and regulations

### Air clearances and creepage distances

Standards/regulations	IEC 60664-1
-----------------------	-------------

## Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------

# CT-TERMIBLOCK 10 DA - Screw termination block



0441711

<https://www.phoenixcontact.com/us/products/0441711>

## Classifications

### ECLASS

ECLASS-11.0	27130815
ECLASS-13.0	27171503

### ETIM

ETIM 9.0	EC001466
----------	----------

### UNSPSC

UNSPSC 21.0	39121600
-------------	----------

# CT-TERMIBLOCK 10 DA - Screw termination block



0441711  
<https://www.phoenixcontact.com/us/products/0441711>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)