

https://www.phoenixcontact.com/us/products/0601292



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Test plug strip, number of positions: 1, color: silver

Your advantages

- Test sockets PSB ... are used for a reliable test pick-off
- With PSB 6/5/6, the test plug with a 4 mm diameter is used
- · All test sockets are screwed into the bridge shaft

Commercial data

Item number	0601292
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE19
Product key	BE1Z3X
Catalog page	Page 590 (C-1-2019)
GTIN	4017918003012
Weight per piece (including packing)	0.965 g
Weight per piece (excluding packing)	0.965 g
Customs tariff number	85366990
Country of origin	PL



https://www.phoenixcontact.com/us/products/0601292



Technical data

Product properties

Product type	Test socket
Number of positions	1

Connection data

Test socket torque	M3
Connection method	Plug-in connection

Dimensions

Dimensional drawing	12,4
Width	4 mm
Height	10 mm
Pin diameter	2.4 mm
Screw thread	M3

Material specifications

Color	silver
Contact material	Silver-plated brass

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C 80 °C
, , ,	

Mounting

Screw thread	M3



https://www.phoenixcontact.com/us/products/0601292



Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27440313
	ECLASS-12.0	27440313
	ECLASS-13.0	27440313
ETIM		
	ETIM 9.0	EC002255
UN	ISPSC	

20122000

0601292

https://www.phoenixcontact.com/us/products/0601292



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com