

US-WML 14 (25X19) - Cable marker label



0800473

<https://www.phoenixcontact.com/us/products/0800473>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Cable marker label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, cable diameter range: 6.1 ... 14 mm, cable diameter: ≤ 14 mm, lettering field size: 25 x 19 mm, Number of individual labels: 8



Your advantages

- The cable marker labels do not increase the cross section of the cable, allowing the cable to be subsequently drawn through cable ducts, for example
- Quick and easy handling
- Resistant to solvents
- The protective foil is wound over the labeling and provides permanent protection against dirt and abrasion
- US-WML ... cable marker labels consist of a labeling field and a transparent protective foil

Commercial data

Item number	0800473
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BG09
Product key	BG2319
Catalog page	Page 215 (C-3-2019)
GTIN	4046356607056
Weight per piece (including packing)	6.442 g
Weight per piece (excluding packing)	5.1 g
Customs tariff number	39199080
Country of origin	DE

US-WML 14 (25X19) - Cable marker label



0800473

<https://www.phoenixcontact.com/us/products/0800473>

Technical data

Product properties

Product type	Conductor marking
Type	Label

Marking

Number of individual labels	8
Number of individual labels per row	4
Identification technology	Thermal transfer for sheets and cards

Dimensions

Width	63.5 mm
Length	25.4 mm

External dimensions

Outside diameter	5 mm ... 14 mm
------------------	----------------

Material specifications

Adhesive	Acrylic
Color	white
Material	PVC
Base element material	Vinyl film
Components	Silicone-free

Cable/line

External cable diameter	≤ 14.00 mm
	6.1 mm ... 14 mm

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N
Result	Test passed

Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed

US-WML 14 (25X19) - Cable marker label



0800473

<https://www.phoenixcontact.com/us/products/0800473>

Test duration	96 h
---------------	------

Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 100 °C (121 °C)	Test passed

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-01):2020-03 DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Ethanol (99 %) [CAS No. 64-17-5]	Test passed
Acetone (99 %) [CAS No. 67-64-1]	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Diesel [CAS No. 68476-34-6]	Test passed
IRM 901	Test passed
IRM 902	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (assembly)	> 0 °C
Permissible humidity (storage/transport)	50 %
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

US-WML 14 (25X19) - Cable marker label



0800473

<https://www.phoenixcontact.com/us/products/0800473>

Shelf life	2 years
------------	---------

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	adhesive
---------------	----------

US-WML 14 (25X19) - Cable marker label



0800473

<https://www.phoenixcontact.com/us/products/0800473>

Classifications

ECLASS

ECLASS-11.0	27281102
ECLASS-12.0	27281102
ECLASS-13.0	27281102

ETIM

ETIM 9.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com