

Conductor marking collar - PMH 4:UNBEDRUCKT - 0800572


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Conductor marking collar, yellow, unlabeled: without print, mounting type: thread on, cable diameter range: 8.5 ... 12 mm, lettering field size: 6.2 x 4 mm



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 017918 006136
GTIN	4017918006136
Weight per Piece (excluding packing)	0.770 g
Custom tariff number	39269097
Country of origin	Czech Republic

Technical data

Dimensions

Length (b)	11 mm
Width (a)	6.2 mm
Height (c)	16.5 mm
Cable diameter	8.5 mm ... 12 mm

Ambient conditions

Ambient temperature (operation)	-45 °C ... 70 °C
Ambient temperature (assembly)	> 10 °C

General

Color	yellow
-------	--------

Conductor marking collar - PMH 4:UNBEDRUCKT - 0800572

Technical data

General

Type	Profile
Components	free from silicone, halogen, and cadmium
Material	Ethylene-vinyl acetate (EVA)
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Printing	without print
Marking mounting type	thread on
Min. cross section	25 mm ²
Max. cross section	35 mm ²
AWG min	4
AWG max	1

Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 10.0.1	27400401
eCl@ss 11.0	27281102
eCl@ss 4.0	27061700
eCl@ss 4.1	27061700
eCl@ss 5.0	27400400
eCl@ss 5.1	27400400
eCl@ss 6.0	27400400
eCl@ss 7.0	27400401
eCl@ss 9.0	27400401

ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC001530
ETIM 6.0	EC001530
ETIM 7.0	EC001530

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410

Conductor marking collar - PMH 4:UNBEDRUCKT - 0800572

Classifications

UNSPSC

UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39131504
UNSPSC 18.0	39131504
UNSPSC 19.0	39131504
UNSPSC 20.0	39131504
UNSPSC 21.0	39131504