

# CES-LTPG-GY - Blind sleeve



0801716

<https://www.phoenixcontact.com/us/products/0801716>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Blind sleeve, large, no. of conductors: 0, type: Blind sleeve, closed, material: SEBS (halogen-free), color: gray, length: 29.5 mm, width: 19.5 mm, height: 17 mm



## Product description

Blind sleeves seal feed-through sections that are not required in CES sealing frames

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 0801716             |
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Sales key                            | BF67                |
| Product key                          | BF7CCX              |
| Catalog page                         | Page 680 (C-2-2019) |
| GTIN                                 | 4046356675178       |
| Weight per piece (including packing) | 33.83 g             |
| Weight per piece (excluding packing) | 34.03 g             |
| Customs tariff number                | 40169997            |
| Country of origin                    | PL                  |

# CES-LTPG-GY - Blind sleeve

0801716

<https://www.phoenixcontact.com/us/products/0801716>




## Technical data

### Product properties

|                   |              |
|-------------------|--------------|
| Product type      | Cable sleeve |
| No. of conductors | 0            |

### Dimensions

|                     |  |
|---------------------|--|
| Dimensional drawing |  |
| Width               | 19.5 mm  |
| Height              | 17 mm  |
| Length              | 29.5 mm  |

### Material specifications

|  |      |
|--|------|
| Material                               | SEBS |
| Flammability rating according to UL 94 | V0   |

### Characteristics

|                         |              |
|-------------------------|--------------|
| Conductor sealing range | Blind sleeve |
| Seal size               | large        |
| Design, Format          | Blind sleeve |
| Design, Cable seal      | closed       |

### Environmental and real-life conditions

#### Ambient conditions

|                                 |  |
|---------------------------------|--|
| Degree of protection            | IP54 (Observe the assembly instructions) |
| Ambient temperature (operation) | -40 °C ... 80 °C (static)                |

### Mounting

|                       |  |
|-----------------------|--|
| Assembly instructions | IP54: for vertical sealing frame mounting/for horizontal sealing frame mounting (downward cable outlet direction). |
|-----------------------|--|

# CES-LTPG-GY - Blind sleeve



0801716

<https://www.phoenixcontact.com/us/products/0801716>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27144425 |
| ECLASS-12.0 | 27144425 |
| ECLASS-13.0 | 27144425 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000451 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# CES-LTPG-GY - Blind sleeve



0801716  
<https://www.phoenixcontact.com/us/products/0801716>

## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)