

# SK U/5,0 WH:UNBEDRUCKT - Marker card



0803922

<https://www.phoenixcontact.com/us/products/0803922>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Marker card, Din A4, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, Office printing systems, mounting type: adhesive, for terminal block width: 210 mm, lettering field size: 186 x 5 mm, Number of individual labels: 630



## Your advantages

- The SK labeling range offers self-adhesive marker strips for labeling products that do not have a marker groove
- Labeling service: Phoenix Contact can custom-label all SK ... markers in accordance with your requirements
- Ideal for labeling COMBICON connectors

## Commercial data

Item number	0803922
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BG12
Product key	BG2114
Catalog page	Page 148 (C-3-2019)
GTIN	4017918007812
Weight per piece (including packing)	17.16 g
Weight per piece (excluding packing)	15.26 g
Customs tariff number	39199080
Country of origin	DE

## Technical data

### Notes

General	Print image may vary depending on laser printer
---------	---

### Product properties

Product type	Terminal marking
Pitch	210 mm
Type	Label

### Marking

Number of individual labels	630
Number of individual labels per row	18
Number of marker strips	35
Identification technology	Office laser printing

### Dimensions

Height	5 mm
Length	186 mm
Pitch	210 mm

### Material specifications

Foil strength	50 µm
Adhesive strength	20 µm
Adhesive	Acrylic
Color	white
Material	Polyester
Components	free from silicone and halogen

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N
Result	Test passed

#### Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed

# SK U/5,0 WH:UNBEDRUCKT - Marker card



0803922

<https://www.phoenixcontact.com/us/products/0803922>

Test duration	96 h
---------------	------

## Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 200 °C (230 °C)	Test passed

## Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-01):2020-03 DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Ethanol (99 %) [CAS No. 64-17-5]	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h
Diesel [CAS No. 68476-34-6]	Test passed
IRM 901	Test passed
IRM 902	Test passed

## Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

## Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

## Ambient conditions

Ambient temperature (operation)	-20 °C ... 80 °C
Ambient temperature (assembly)	> 0 °C
Recommended storage conditions	20 ... 25 °C / 40 ... 50 % relative humidity.
Recommended ambient temperature (storage/transport)	20 °C ... 25 °C
Recommended humidity (storage/transport)	40 % ... 50 %
Shelf life	2 years

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

# SK U/5,0 WH:UNBEDRUCKT - Marker card



0803922

<https://www.phoenixcontact.com/us/products/0803922>

## Mounting

Mounting type	adhesive
---------------	----------

0803922

<https://www.phoenixcontact.com/us/products/0803922>

## Classifications

### ECLASS

ECLASS-11.0	27281101
ECLASS-12.0	27281101
ECLASS-13.0	27281101

### ETIM

ETIM 9.0	EC000761
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)