

SK 5/3,8:UNBEDRUCKT - Marker card



0805409

<https://www.phoenixcontact.com/us/products/0805409>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Marker card, Sheet, white, unlabeled, can be labeled with: Marker pen: without print, mounting type: adhesive, for terminal block width: 5 mm, lettering field size: 5□x□3.8□mm, Number of individual labels: 120



Commercial data

| | |
|--------------------------------------|--------------------|
| Item number | 0805409 |
| Packing unit | 10 pc |
| Minimum order quantity | 1 pc |
| Product key | BG2113 |
| Catalog page | Page 502 (CL-2009) |
| GTIN | 4017918129187 |
| Weight per piece (including packing) | 0.82 g |
| Weight per piece (excluding packing) | 0.714 g |
| Country of origin | PL |

Technical data

Notes

| | |
|---------|-------------------------|
| General | Can be labeled with CMS |
|---------|-------------------------|

Product properties

| | |
|--------------|------------------|
| Product type | Terminal marking |
| Pitch | 5 mm |
| Type | Label |

Marking

| | |
|-------------------------------------|---------------|
| Number of individual labels | 120 |
| Number of individual labels per row | 10 |
| Number of marker strips | 12 |
| Printing | without print |
| Identification technology | manually |

Dimensions

| | |
|--------|--------|
| Width | 5 mm |
| Height | 3.8 mm |
| Pitch | 5 mm |

Material specifications

| | |
|-------------------|--------------------------------|
| Foil strength | 53 µm |
| Adhesive strength | 20 µm |
| Adhesive | Acrylic |
| Color | white |
| Material | Polyester |
| Components | free from silicone and halogen |

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

| | |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

UV resistance

| | |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
| Result | Test passed |
| Test duration | 96 h |

Wipe resistance of inscriptions

| | |
|--------------------------------|--|
| Specification | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
| Isopropyl [CAS No. 67-63-0] | Test passed |

SK 5/3,8:UNBEDRUCKT - Marker card



0805409

<https://www.phoenixcontact.com/us/products/0805409>

| | |
|---|-------------|
| n-Hexane [CAS No. 110-54-3] | Test passed |
| Water + Petroleum ether [CAS No. 64742-82-1] | Test passed |

Testing in a condensation changing climate in the presence of sulfur dioxide

| | |
|---------------|-------------------|
| Specification | DIN 50018:2013-05 |
| Result | Test passed |
| Climate level | AHT 1.0 S |
| Cycles | 2 |

Salt spray test

| | |
|---------------|---------------------------|
| Specification | DIN EN 60068-2-11:2000-02 |
| Result | Test passed |

Ambient conditions

| | |
|---|--|
| Ambient temperature (operation) | -40 °C ... 150 °C |
| Ambient temperature (assembly) | > 15 °C |
| Recommended storage conditions | 23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing. |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % |
| Shelf life | 12 months |

Standards and regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

Mounting

| | |
|---------------|----------|
| Mounting type | adhesive |
|---------------|----------|

SK 5/3,8:UNBEDRUCKT - Marker card



0805409

<https://www.phoenixcontact.com/us/products/0805409>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27281101 |
| ECLASS-12.0 | 27281101 |
| ECLASS-13.0 | 27281101 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000761 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com