

# GPE 27X 8 SR/R - Engraving material



0806877

<https://www.phoenixcontact.com/us/products/0806877>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Engraving material, Sheet, silver, unlabeled, can be labeled with: PLOTMARK, ENGRAVING UNIT, CMS-P1-PLOTTER, P1 ENGRAVING UNIT, mounting type: adhesive, lettering field size: 27 x 8 mm, Number of individual labels: 66



## Your advantages

- Labeling service: Phoenix Contact can custom-label all GPE ... markers according to your requirements
- The adhesive foil used ensures good adhesive properties, even on uneven surfaces
- Two-layer material
- The label sheet consists of prefabricated, individual self-adhesive labels
- Can be engraved using the P1 ENGRAVING UNIT
- Can be labeled easily using the CMS-P1-PLOTTER

## Commercial data

Item number	0806877
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BG19
Product key	BG2415
Catalog page	Page 346 (C-3-2019)
GTIN	4017918145002
Weight per piece (including packing)	18.43 g
Weight per piece (excluding packing)	18.43 g
Customs tariff number	39203000
Country of origin	DE

# GPE 27X 8 SR/R - Engraving material



0806877

<https://www.phoenixcontact.com/us/products/0806877>

## Technical data

### Product properties

Product type	Device marking
--------------	----------------

### Marking

Number of individual labels	66
Number of individual labels per row	3

### Mounting

Mounting type	adhesive
---------------	----------

### Material specifications

Adhesive strength	50 µm
Adhesive	Acrylic
Color	silver
Material	TRANSPLY-ABS
Components	free from silicone and halogen

### Environmental and real-life conditions


#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 85 °C
Recommended storage conditions	20°C/50% relative humidity. Storage in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	20 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

### Dimensions

Dimensional drawing	
Width	27 mm
Height	8 mm
Length	8 mm
Material strength	0.80 mm

### Standards and regulations

# GPE 27X 8 SR/R - Engraving material



0806877

<https://www.phoenixcontact.com/us/products/0806877>

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

## Notes

General	Can be labeled with CMS
---------	-------------------------

# GPE 27X 8 SR/R - Engraving material



0806877

<https://www.phoenixcontact.com/us/products/0806877>

## Classifications

### ECLASS

ECLASS-11.0	27281103
ECLASS-12.0	27281103
ECLASS-13.0	27281103

### ETIM

ETIM 9.0	EC001288
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)