

# ESL 62X10 - Insert strip



0809492

<https://www.phoenixcontact.com/us/products/0809492>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems, CMS-P1-PLOTTER, mounting type: insert, lettering field size: 62 x 10 mm, Number of individual labels: 72



## Your advantages

- The material file can be downloaded under the CLIP PROJECT software under Downloads - "Software update - Marking"
- Insert labels for plastic cable markers

## Commercial data

Item number	0809492
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG13
Product key	BG2414
Catalog page	Page 332 (NTK-2010)
GTIN	4017918194420
Weight per piece (including packing)	31.42 g
Weight per piece (excluding packing)	31.42 g
Customs tariff number	39206219
Country of origin	DE

# ESL 62X10 - Insert strip



0809492

<https://www.phoenixcontact.com/us/products/0809492>

## Technical data

### Notes

General	Print image may vary depending on laser printer
---------	-------------------------------------------------

### Product properties

Product type	Terminal marking
--------------	------------------

### Marking

Number of individual labels	72
Number of individual labels per row	3

### Dimensions

Width	62 mm
Length	10 mm

### Material specifications

Color	white
Material	Polyester foil
Components	free from silicone and halogen

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2011 (following)
Requirements	≥ 5 N
Result	Test passed

#### Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

#### Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

#### Salt spray test

# ESL 62X10 - Insert strip



0809492

<https://www.phoenixcontact.com/us/products/0809492>

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

## Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

## Mounting

Mounting type	insert
---------------	--------

# ESL 62X10 - Insert strip



0809492

<https://www.phoenixcontact.com/us/products/0809492>

## Classifications

### ECLASS

ECLASS-11.0	27281106
ECLASS-12.0	27281106
ECLASS-13.0	27281106

### ETIM

ETIM 9.0	EC001530
----------	----------

### UNSPSC

UNSPSC 21.0	39131700
-------------	----------

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)