

# STP 4-2 - Marker carriers

0810575

<https://www.phoenixcontact.com/us/products/0810575>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker carriers, snaps into ST 1,5... spring-cage terminal blocks, can be marked with UC-TM 4, UC-TMF 4, UCT-TM 4, UCT-TMF 4, ZB 4, or ZBF 4, gray, unlabeled, mounting type: plug in, lettering field size: 4 x 10.5 mm

## Your advantages

- The labeling areas of wired multi-level terminal blocks are increased by using marker carriers
- Depending on version, the marker carriers are inserted in the holders on the upper terminal block level

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 0810575             |
| Packing unit                         | 100 pc              |
| Minimum order quantity               | 100 pc              |
| Sales key                            | BG12                |
| Product key                          | BG211A              |
| Catalog page                         | Page 154 (C-3-2019) |
| GTIN                                 | 4017918877941       |
| Weight per piece (including packing) | 0.42 g              |
| Weight per piece (excluding packing) | 0.37 g              |
| Customs tariff number                | 39269097            |
| Country of origin                    | PL                  |

# STP 4-2 - Marker carriers



0810575

<https://www.phoenixcontact.com/us/products/0810575>

## Technical data

### Product properties

|              |                 |
|--------------|-----------------|
| Product type | Marker carriers |
|--------------|-----------------|

### Dimensions

|        |         |
|--------|---------|
| Width  | 4 mm    |
| Height | 28.6 mm |
| Length | 24.9 mm |

### Material specifications

|  |                                |
|--|--------------------------------|
| Color                                  | gray                           |
| Material                               | PA                             |
| Flammability rating according to UL 94 | V2                             |
| Components                             | free from silicone and halogen |

### Environmental and real-life conditions

#### Ambient conditions

|   |                   |
|---|-------------------|
| Ambient temperature (operation)                     | -40 °C ... 100 °C |
| Recommended ambient temperature (storage/transport) | 23 °C             |
| Recommended humidity (storage/transport)            | 50 %              |

### Mounting

|               |         |
|---------------|---------|
| Mounting type | plug in |
|---------------|---------|

# STP 4-2 - Marker carriers



0810575

<https://www.phoenixcontact.com/us/products/0810575>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27281105 |
| ECLASS-12.0 | 27281105 |
| ECLASS-13.0 | 27281105 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001530 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)