

# GPEG SO - Engraving material



0811794

<https://www.phoenixcontact.com/us/products/0811794>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Engraving material, Sheet, according to customer requirement, labeled according to customer specifications, mounting type: adhesive, lettering field size: 293 x 277 mm



## Commercial data

Item number	0811794
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG2415
GTIN	4017918929688
Weight per piece (including packing)	152.44 g
Weight per piece (excluding packing)	152.44 g
Country of origin	PL

## Technical data

### Product properties

Product type	Labeled device marker
--------------	-----------------------

### Environmental and real-life conditions

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
---------------	--------------------------------

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 85 °C
Recommended storage conditions	20°C/50% relative humidity. Storage in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	20 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

### Mounting

Mounting type	adhesive
---------------	----------

### Material specifications

Adhesive strength	50 µm
Adhesive	Acrylic
Color	according to customer requirement
Material	ABS
Components	Silicone-free

### Environmental and real-life conditions

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
---------------	--------------------------------

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 85 °C
Recommended storage conditions	20°C/50% relative humidity. Storage in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	20 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

### Dimensions

Width	300 mm
Length	280 mm
Material strength	0.80 mm

# GPEG SO - Engraving material



0811794  
<https://www.phoenixcontact.com/us/products/0811794>

## Classifications

### ECLASS

ECLASS-11.0	27281103
ECLASS-12.0	27281103
ECLASS-13.0	27281103

### ETIM

ETIM 9.0	EC001288
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)