GPAL 400X300X1,5 SR/BK/GD - Engraving plate for outdoor use



0814034

https://www.phoenixcontact.com/us/products/0814034

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Engraving plate for outdoor use, Plate, silver/black, labeled according to customer specifications, can be labeled with: P1 ENGRAVING UNIT, ENGRAVING UNIT, mounting type: screw, rivet, lettering field size: 400 x 300 mm



Commercial data

| Item number | 0814034 |
|--------------------------------------|---------------|
| Packing unit | 5 pc |
| Minimum order quantity | 5 pc |
| Sales key | BG19 |
| Product key | BG2415 |
| GTIN | 4017918977757 |
| Weight per piece (including packing) | 381.566 g |
| Weight per piece (excluding packing) | 292.9 g |
| Customs tariff number | 76169990 |
| Country of origin | DE |

GPAL 400X300X1,5 SR/BK/GD - Engraving plate for outdoor use



0814034

https://www.phoenixcontact.com/us/products/0814034

Technical data

| Р | rodi | ıct | properties | |
|---|------|-----|-------------|--|
| г | ıouı | JUL | DI ODEI HES | |

| Product type | Labeled device marker | |
|---------------------------|-----------------------|--|
| Marking | | |
| Identification technology | Engraving | |

Environmental and real-life conditions

UV resistance

Specification

| Ambient conditions | | |
|---|---|--|
| Ambient temperature (operation) | -20 °C 85 °C | |
| Recommended ambient temperature (storage/transport) | 23 °C | |
| Recommended humidity (storage/transport) | 50 % (Storage in a dry and dark place in the original packaging is recommended) | |

ISO 4892-2:2013-03 (following)

Mounting

| Mounting type screw, rivet |
|----------------------------|
|----------------------------|

Material specifications

| Color silver/black | |
|--------------------|--|
|--------------------|--|

Environmental and real-life conditions

UV resistance

| Specification | ISO 4892-2:2013-03 (following) | |
|---|---|--|
| Ambient conditions | | |
| Ambient temperature (operation) | -20 °C 85 °C | |
| Recommended ambient temperature (storage/transport) | 23 °C | |
| Recommended humidity (storage/transport) | 50 % (Storage in a dry and dark place in the original packaging is recommended) | |

Dimensions

| Width | 400 mm |
|--------|--------|
| Length | 300 mm |

GPAL 400X300X1,5 SR/BK/GD - Engraving plate for outdoor use



0814034

https://www.phoenixcontact.com/us/products/0814034

Classifications

ECLASS

| | ECLASS-11.0 | 27281103 | |
|--------|-------------|----------|--|
| | ECLASS-12.0 | 27281103 | |
| | ECLASS-13.0 | 27281103 | |
| ETIM | | | |
| | IIVI | | |
| | ETIM 9.0 | EC001288 | |
| UNSPSC | | | |
| | UNSPSC 21.0 | 39131500 | |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com