# KLM 3-L - Terminal strip marker carrier



https://www.phoenixcontact.com/us/products/0814788



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Terminal strip marker carrier, adjustable height, for CLIPFIX 15, CLIPFIX 35, and CLIPFIX 35-5 end brackets, can be marked using labels in  $20 \times 8$  mm format

## Your advantages

- The KLM range has been specifically developed for CLIPFIX end brackets
- · The precise engagement mechanism enables infinite adjustment of the labeling area height
- The KLM 3-L is suitable for multi-level terminal blocks and can be cut at two defined points

#### Commercial data

| Item number                          | 0814788             |
|--------------------------------------|---------------------|
| Packing unit                         | 100 pc              |
| Minimum order quantity               | 100 pc              |
| Sales key                            | BG12                |
| Product key                          | BG211A              |
| Catalog page                         | Page 540 (C-3-2019) |
| GTIN                                 | 4046356014069       |
| Weight per piece (including packing) | 0.966 g             |
| Weight per piece (excluding packing) | 0.9 g               |
| Customs tariff number                | 39269097            |
| Country of origin                    | DE                  |

# KLM 3-L - Terminal strip marker carrier



0814788

https://www.phoenixcontact.com/us/products/0814788

## Technical data

### Product properties

|            | Product type     | Marker carriers |  |  |
|------------|------------------|-----------------|--|--|
| Dimensions |                  |                 |  |  |
|            | Width            | 10 mm           |  |  |
|            | Height           | 73.8 mm         |  |  |
|            | Height NS 35/7,5 | 12 mm           |  |  |
|            | Length           | 22 mm           |  |  |

### Material specifications

| Color  | gray         |
|--|--------------|
| Material   | PA           |
| Flammability rating according to UL 94                           | V2           |
| Relative insulation material temperature index (Elec., UL 746 B) | 125 °C       |
| Components   | halogen-free |

### Environmental and real-life conditions

#### Ambient conditions

| Ambient temperature (operation)                     | -40 °C 100 °C |
|---|---------------|
| Recommended ambient temperature (storage/transport) | 23 °C         |
| Recommended humidity (storage/transport)            | 50 %          |

## Mounting

| Mounting type | plug in |
|---------------|---------|
|---------------|---------|

# KLM 3-L - Terminal strip marker carrier



0814788

https://www.phoenixcontact.com/us/products/0814788

## Classifications

#### **ECLASS**

|        | ECLASS-11.0 | 27281105 |  |  |
|--------|-------------|----------|--|--|
|        | ECLASS-12.0 | 27281105 |  |  |
|        | ECLASS-13.0 | 27281105 |  |  |
| ETIM   |             |          |  |  |
|        | ETIM 9.0    | EC001530 |  |  |
| UNSPSC |             |          |  |  |
|        | UNSPSC 21.0 | 39121400 |  |  |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com