

# GPE 20X 7 WH CUS - Engraving material




0824416

<https://www.phoenixcontact.com/us/products/0824416>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Engraving material, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 7 mm, Number of individual labels: 100



## Your advantages

- Labeling service: Phoenix Contact can custom-label all GPE ... markers according to your requirements
- The adhesive foil used ensures good adhesive properties, even on uneven surfaces
- Two-layer material
- The label sheet consists of prefabricated, individual self-adhesive labels

## Commercial data

Item number	0824416
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8145
Catalog page	Page 294 (C-5-2013)
GTIN	4046356352864
Weight per piece (including packing)	21.69 g
Weight per piece (excluding packing)	21.5 g
Country of origin	PL

## Technical data

### Product properties

Product type	Labeled device marker
--------------	-----------------------

### Marking

Number of individual labels	100
Number of individual labels per row	4
Identification technology	Engraving

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 85 °C
Recommended storage conditions	20°C/50% relative humidity. Storage in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	20 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

### Mounting

Mounting type	adhesive
---------------	----------

### Material specifications

Adhesive strength	50 µm
Adhesive	Acrylic
Color	white
Material	TRANSPLY-ABS
Components	free from silicone and halogen

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 85 °C
Recommended storage conditions	20°C/50% relative humidity. Storage in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	20 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

### Dimensions

Width	20 mm
Length	7 mm
Material strength	0.80 mm

### Standards and regulations

# GPE 20X 7 WH CUS - Engraving material



0824416

<https://www.phoenixcontact.com/us/products/0824416>

Wipe resistance

DIN EN 61010-1 (VDE 0411-1)

# GPE 20X 7 WH CUS - Engraving material



0824416

<https://www.phoenixcontact.com/us/products/0824416>

## Classifications

### ECLASS

ECLASS-11.0	27281103
ECLASS-12.0	27281103
ECLASS-13.0	27281103

### ETIM

ETIM 9.0	EC001288
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)