

0824424

https://www.phoenixcontact.com/us/products/0824424

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Engraving material, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 27 x 18 mm, Number of individual labels: 30



Your advantages

- · Labeling service: Phoenix Contact can custom-label all GPE ... markers according to your requirements
- · The adhesive foil used ensures good adhesive properties, even on uneven surfaces
- · Two-layer material
- · The label sheet consists of prefabricated, individual self-adhesive labels

Commercial data

Item number	0824424
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8145
Catalog page	Page 294 (C-5-2013)
GTIN	4046356352949
Weight per piece (including packing)	21.69 g
Weight per piece (excluding packing)	21.5 g
Country of origin	PL



0824424

https://www.phoenixcontact.com/us/products/0824424

Technical data

Product properties

Product type	Labeled device marker
Marking	
Number of individual labels	30
Number of individual labels per row	3
Identification technology	Engraving

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C 85 °C
Recommended storage conditions	20°C/50% relative humidity. Storage in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	20 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

Mounting

Mounting type	adhesive
---------------	----------

Material specifications

Adhesive strength	50 μm
Adhesive	Acrylic
Color	white
Material	TRANSPLY-ABS
Components	free from silicone and halogen

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C 85 °C
Recommended storage conditions	20°C/50% relative humidity. Storage in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	20 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

Dimensions

Width	27 mm
Length	18 mm
Material strength	0.80 mm

Standards and regulations



0824424

https://www.phoenixcontact.com/us/products/0824424

Wipe resistance DIN EN 61010-1 (VDE 0411-1)



0824424

https://www.phoenixcontact.com/us/products/0824424

Classifications

ECLASS

ECLASS-11.0	27281103
ECLASS-12.0	27281103
ECLASS-13.0	27281103
ETIM	
ETIM 9.0	EC001288
UNSPSC	
UNSPSC 21.0	39131500

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com