

# KMT 24X10 WH 200 CUS - Cable marker



0824438

<https://www.phoenixcontact.com/us/products/0824438>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable marker, can be ordered: by line, white, labeled according to customer specifications, mounting type: Assembly with cable ties, cable diameter: > 10 mm, lettering field size: 24 x 8 mm

## Commercial data

Item number	0824438
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8131
GTIN	4046356353069
Weight per piece (including packing)	1.99 g
Weight per piece (excluding packing)	1.99 g
Country of origin	PL

# KMT 24X10 WH 200 CUS - Cable marker



0824438

<https://www.phoenixcontact.com/us/products/0824438>

## Technical data

### Product properties

Product type	Labeled conductor marker
Type	Roll

### Marking

Identification technology	Thermal transfer for rolls
---------------------------	----------------------------

### Mounting

Mounting type	Assembly with cable ties
---------------	--------------------------

### Material specifications

Color	white
Material	Polyester foil

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N
Result	Test passed

#### Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

#### Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 100 °C (121 °C)	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h
Diesel [CAS No. 68476-34-6]	Test passed
IRM 901	Test passed
IRM 902	Test passed

#### Testing in a condensation changing climate in the presence of sulfur dioxide

# KMT 24X10 WH 200 CUS - Cable marker



0824438

<https://www.phoenixcontact.com/us/products/0824438>

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

## Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

## Ambient conditions

Ambient temperature (operation)	-60 °C ... 120 °C
Recommended ambient temperature (storage/transport)	≤ 27 °C
Recommended humidity (storage/transport)	≤ 60 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	2 years

## Dimensions

Width	10 mm
Length	24 mm

## External dimensions

Outside diameter	10 mm ... 136 mm
------------------	------------------

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

# KMT 24X10 WH 200 CUS - Cable marker



0824438

<https://www.phoenixcontact.com/us/products/0824438>

## Classifications

### ECLASS

ECLASS-11.0	27281102
ECLASS-12.0	27281102
ECLASS-13.0	27281102

### ETIM

ETIM 9.0	EC001530
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)