


SK 3,8 REEL P6,2 WH CUS - Marker card



0825126

<https://www.phoenixcontact.com/us/products/0825126>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker card, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, for terminal block width: 6.2 mm, lettering field size: continuous x 3.8 mm

Your advantages

- Labeling service: Phoenix Contact can custom-label all SK ... markers in accordance with your requirements
- The SK labeling range offers self-adhesive marker strips for labeling products that do not have a marker groove

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 0825126 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | BG24 |
| Product key | BG8113 |
| Catalog page | Page 103 (C-5-2013) |
| GTIN | 4046356355094 |
| Weight per piece (including packing) | 1.04 g |
| Weight per piece (excluding packing) | 1.04 g |
| Customs tariff number | 49119900 |
| Country of origin | DE |

Technical data

Product properties

| | |
|--------------|-------------------------|
| Product type | Labeled terminal marker |
| Pitch | 6.2 mm |
| Type | Label |

Marking

| | |
|-------------------------|----|
| Number of marker strips | 12 |
|-------------------------|----|

Mounting

| | |
|---------------|----------|
| Mounting type | adhesive |
|---------------|----------|

Material specifications

| | |
|-------------------|--------------------------------|
| Foil strength | 53 µm |
| Adhesive strength | 20 µm |
| Adhesive | Acrylic |
| Color | white |
| Material | Polyester |
| Components | free from silicone and halogen |

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

| | |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

UV resistance

| | |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
| Result | Test passed |
| Test duration | 96 h |

Ambient conditions

| | |
|---|--|
| Ambient temperature (operation) | -40 °C ... 150 °C |
| Ambient temperature (assembly) | > 15 °C |
| Recommended storage conditions | 23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing. |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % |
| Shelf life | 12 months |

Dimensions

| | |
|--------|--------|
| Height | 3.8 mm |
| Pitch | 6.2 mm |

Standards and regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

SK 3,8 REEL P6,2 WH CUS - Marker card



0825126

<https://www.phoenixcontact.com/us/products/0825126>

Notes

General

Marking up to max. 25-pos.

SK 3,8 REEL P6,2 WH CUS - Marker card



0825126

<https://www.phoenixcontact.com/us/products/0825126>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27281101 |
| ECLASS-12.0 | 27281101 |
| ECLASS-13.0 | 27281101 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000761 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com