


# SK 5,0 REEL P12,5 WH CUS - Marker card



0825130

<https://www.phoenixcontact.com/us/products/0825130>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker card, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, for terminal block width: 12.5 mm, lettering field size: continuous x 5 mm

## Commercial data

Item number	0825130
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8113
GTIN	4046356355117
Weight per piece (including packing)	1.99 g
Weight per piece (excluding packing)	1.99 g
Country of origin	PL

# SK 5,0 REEL P12,5 WH CUS - Marker card



0825130

<https://www.phoenixcontact.com/us/products/0825130>

## Technical data

### Product properties

Product type	Labeled terminal marker
Pitch	12.5 mm
Type	Label

### Marking

Number of marker strips	10
-------------------------	----

### Mounting

Mounting type	adhesive
---------------	----------

### Material specifications

Foil strength	53 µm
Adhesive strength	20 µm
Adhesive	Acrylic
Color	white
Material	Polyester
Components	free from silicone and halogen

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 150 °C
Ambient temperature (assembly)	> 15 °C
Recommended storage conditions	23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

### Dimensions

Height	5 mm
Pitch	12.5 mm

### Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

# SK 5,0 REEL P12,5 WH CUS - Marker card



0825130

<https://www.phoenixcontact.com/us/products/0825130>

## Notes

General

Marking up to max. 25-pos.

# SK 5,0 REEL P12,5 WH CUS - Marker card



0825130

<https://www.phoenixcontact.com/us/products/0825130>

## Classifications

### ECLASS

ECLASS-11.0	27281101
ECLASS-12.0	27281101
ECLASS-13.0	27281101

### ETIM

ETIM 9.0	EC000761
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)