

# SD-WMTBS (NEUTRAL) CC - Conductor marking collar



0826637

<https://www.phoenixcontact.com/us/products/0826637>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Conductor marking collar, yellow: without print, mounting type: slide-on, cable diameter: > 16 mm, lettering field size: 4.3 x 26 mm

## Your advantages

- The printed individual markers are pushed onto the corresponding holders
- Cable markers for marking cables and conductors with larger cross sections

## Commercial data

Item number	0826637
Packing unit	100 pc
Minimum order quantity	100 pc
Product key	BG2312
Catalog page	Page 245 (C-3-2019)
GTIN	4046356414494
Weight per piece (including packing)	0.157 g
Weight per piece (excluding packing)	0.143 g
Country of origin	SE

# SD-WMTBS (NEUTRAL) CC - Conductor marking collar



0826637

<https://www.phoenixcontact.com/us/products/0826637>

## Technical data

### Product properties

Product type	Labeled conductor marker
Type	Marking strip/label

### Marking

Printing	without print
----------	---------------

### Mounting

Mounting type	slide-on
---------------	----------

### Material specifications

Color	yellow
Material	PVC
Flammability rating according to UL 94	V2
Components	Free from silicone and cadmium

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

#### Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07 DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed

#### Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

#### Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

# SD-WMTBS (NEUTRAL) CC - Conductor marking collar



0826637

<https://www.phoenixcontact.com/us/products/0826637>

## Ambient conditions

Ambient temperature (operation)	-30 °C ... 60 °C
---------------------------------	------------------

## Dimensions

Width	4.3 mm
Length	11.3 mm

## External dimensions

Outside diameter	> 10 mm ... 136 mm
------------------	--------------------

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

## Notes

General	Please specify the required marking with order: Minimum order per imprint: 1 packing unit
---------	---

# SD-WMTBS (NEUTRAL) CC - Conductor marking collar



0826637

<https://www.phoenixcontact.com/us/products/0826637>

## Classifications

### ECLASS

ECLASS-11.0	27281102
ECLASS-12.0	27281102
ECLASS-13.0	27281102

### ETIM

ETIM 9.0	EC001530
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)