ZBF 16:UNPRINTED - Zack Marker strip, flat

0827464

https://www.phoenixcontact.com/us/products/0827464

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 16 mm, lettering field size: 16. 25 x 10.5 mm, Number of individual labels: 50

Your advantages

- · Unlabeled marking strips can be custom-labeled with a plotter or by hand
- · Other pitches available on request
- The ZBF zack marker strip system with flat marker groove is a marking solution for modular terminal blocks and electronics modules
- · The multi-section marking strips are easy to fit and can be easily separated if required

Commercial data

| Item number | 0827464 |
|--------------------------------------|---------------------|
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | BG05 |
| Product key | BG2112 |
| Catalog page | Page 131 (C-3-2019) |
| GTIN | 4046356431439 |
| Weight per piece (including packing) | 0.71 g |
| Weight per piece (excluding packing) | 0.7 g |
| Customs tariff number | 39269097 |
| Country of origin | DE |

ZBF 16:UNPRINTED - Zack Marker strip, flat

0827464

https://www.phoenixcontact.com/us/products/0827464

Technical data

Notes

| | General | Can be labeled with CMS | | |
|-------------------------|--|--------------------------------|--|--|
| | General | Can be labeled with CMS | | |
| | | | | |
| Product properties | | | | |
| | Product type | Terminal marking | | |
| | Pitch | 16 mm | | |
| | Туре | flat | | |
| Marking | | | | |
| | Number of individual labels | 50 | | |
| | Number of individual labels per row | 5 | | |
| | Number of marker strips | 10 | | |
| Dimensions | | | | |
| | Width | 16 mm | | |
| | Pitch | 16 mm | | |
| Material specifications | | | | |
| | Color | white | | |
| | Material | PA | | |
| | Flammability rating according to UL 94 | V2 | | |
| | Components | free from silicone and halogen | | |
| | | | | |

Environmental and real-life conditions

| Specification | ISO 4892-2:2013-03 (following) |
|---|--------------------------------|
| Ambient conditions | |
| Ambient temperature (operation) | -40 °C 100 °C |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % |
| andards and regulations Wipe resistance | |
| | DIN EN 61010-1 (VDE 0411-1) |



0827464

https://www.phoenixcontact.com/us/products/0827464



Classifications

ECLASS

| ECLASS-12.0 27281101 | ECLASS-11.0 | 27281101 | |
|----------------------|-------------|----------|--|
| ECLASS 12.0 27091101 | ECLASS-12.0 | 27281101 | |
| ECLA33-13.0 27201101 | ECLASS-13.0 | 27281101 | |

ETIM

| | ETIM 9.0 | EC000761 | | | |
|----|-------------|----------|--|--|--|
| U١ | UNSPSC | | | | |
| | UNSPSC 21.0 | 39131500 | | | |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com