

GPE 1,5 SO - Engraving material



0830149

<https://www.phoenixcontact.com/us/products/0830149>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Engraving material, Sheet, according to customer requirement, labeled according to customer specifications, can be labeled with: PLOTMARK, ENGRAVING UNIT, CMS-P1-PLOTTER, P1 ENGRAVING UNIT, mounting type: adhesive, lettering field size: 184 x 93 mm



Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 0830149 |
| Packing unit | 15 pc |
| Minimum order quantity | 15 pc |
| Note | Made to order (non-returnable) |
| Product key | BG8145 |
| GTIN | 4046356632492 |
| Weight per piece (including packing) | 31.6 g |
| Weight per piece (excluding packing) | 31.6 g |
| Country of origin | PL |

GPE 1,5 SO - Engraving material



0830149

<https://www.phoenixcontact.com/us/products/0830149>

Technical data

Product properties

| | |
|--------------|-----------------------|
| Product type | Labeled device marker |
|--------------|-----------------------|

Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 85 °C |
| Recommended storage conditions | 20°C/50% relative humidity. Storage in the original packaging is recommended. |
| Recommended ambient temperature (storage/transport) | 20 °C |
| Recommended humidity (storage/transport) | 50 % |
| Shelf life | 12 months |

Mounting

| | |
|---------------|----------|
| Mounting type | adhesive |
|---------------|----------|

Material specifications

| | |
|-------------------|-----------------------------------|
| Adhesive strength | 50 µm |
| Adhesive | Acrylic |
| Color | according to customer requirement |
| Material | Polyester |
| Components | free from silicone and halogen |

Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 85 °C |
| Recommended storage conditions | 20°C/50% relative humidity. Storage in the original packaging is recommended. |
| Recommended ambient temperature (storage/transport) | 20 °C |
| Recommended humidity (storage/transport) | 50 % |
| Shelf life | 12 months |

Dimensions

| | |
|-------------------|---------|
| Width | 100 mm |
| Length | 195 mm |
| Material strength | 1.50 mm |

Standards and regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

GPE 1,5 SO - Engraving material



0830149

<https://www.phoenixcontact.com/us/products/0830149>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27281103 |
| ECLASS-12.0 | 27281103 |
| ECLASS-13.0 | 27281103 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001288 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com