

0830370

https://www.phoenixcontact.com/us/products/0830370

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Markers for sticking on, screwing or riveting, can be ordered: by card, silver, labeled according to customer specifications, mounting type: adhere, screw, rivet, adhesive, lettering field size: 28 x 10 mm, Number of individual labels: 26



Your advantages

- · The stick-on UniSheet markers can also be attached with screws or rivets
- The perforated markers and labels are easy to separate and can be easily fitted

Commercial data

Item number	0830370
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8149
Catalog page	Page 267 (C-5-2013)
GTIN	4046356723541
Weight per piece (including packing)	18.44 g
Weight per piece (excluding packing)	18.44 g
Country of origin	PL



0830370

https://www.phoenixcontact.com/us/products/0830370

Technical data

Product properties

Product type	Labeled device marker	
Marking		
Number of individual labels	26	
Number of individual labels per row	2	

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed	
UV resistance		
Specification	ISO 4892-2:2013-03 (following)	
Result	Test passed	
Test duration	96 h	
Ambient conditions Ambient temperature (operation) -30 °C 80 °C		
Recommended storage conditions	20 °C / 50 % relative humidity.	
Recommended ambient temperature (storage/transport)	20 °C	
Recommended humidity (storage/transport)	50 %	
Shelf life	12 months	

Mounting

Mounting type	adhere, screw, rivet
---------------	----------------------

Material specifications

RoHS compliant	yes
Foil strength	500 μm
Adhesive strength	250 μm
Adhesive	Acrylic
Color	silver
Material	PVC
Flammability rating according to UL 94	V0
Components	Silicone-free

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish



0830370

https://www.phoenixcontact.com/us/products/0830370

Specification	ISO 4892-2:2013-03 (following)	
Result	Test passed	
Test duration	96 h	
Ambient conditions		
Ambient temperature (operation)	-30 °C 80 °C	
Recommended storage conditions	20 °C / 50 % relative humidity.	
Recommended ambient temperature (storage/transport)	20 °C	
Recommended humidity (storage/transport)	50 %	
Shelf life	12 months	
Dimensions		
Width	28 mm	
Height	0.5 mm	
Length	10 mm	
Standards and regulations		
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)	



0830370

https://www.phoenixcontact.com/us/products/0830370

Classifications

ECLASS

	ECLASS-11.0	27281103
	ECLASS-12.0	27281103
	ECLASS-13.0	27281103
ETIM		
	ETIM 9.0	EC001288
UNSPSC		
	UNSPSC 21.0	39131500

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com