

# WML 36 (25X38)A4 - Cable marker label



0830697

<https://www.phoenixcontact.com/us/products/0830697>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Cable marker label, Sheet, white, unlabeled, can be labeled with: Office printing systems, CMS-P1-PLOTTER, PLOTMARK, mounting type: adhesive, cable diameter range: 12.1 ... 36.4 mm, cable diameter:  $\leq 36.4$  mm, lettering field size: 25 x 38 mm, Number of individual labels: 14



## Your advantages

- For indoor applications: high resistance to dirt and abrasion due to the protective laminate
- Firmly defined positioning of labels thanks to the adhesive system
- Broad diameter range with many different applications inside and outside the control cabinet
- The protective foil is wound over the labeling and provides permanent protection against dirt and abrasion
- The wrap-around labels do not create any additional volume, so the cable can also be pulled through cable ducts, for example
- For cylindrical objects, single wires, and cables

## Commercial data

Item number	0830697
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	BG2314
Catalog page	Page 216 (C-3-2019)
GTIN	4046356719193
Weight per piece (including packing)	15.88 g
Weight per piece (excluding packing)	15.7 g
Country of origin	DE

# WML 36 (25X38)A4 - Cable marker label



0830697

<https://www.phoenixcontact.com/us/products/0830697>

## Technical data

### Notes

General	Print image may vary depending on laser printer
---------	---

### Product properties

Product type	Conductor marking
Type	Label

### Marking

Number of individual labels	14
Number of individual labels per row	7
Identification technology	Office laser printing

### Dimensions

Width	25 mm
Length	140 mm

### External dimensions

Outside diameter	11 mm ... 36 mm
------------------	-----------------

### Material specifications

RoHS compliant	yes
Adhesive	Acrylic
Color	white
Material	Polyester
Components	Free from halogen and cadmium

### Cable/line

External cable diameter	≤ 36.40 mm
	12.1 mm ... 36.4 mm

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

#### Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S

# WML 36 (25X38)A4 - Cable marker label



0830697

<https://www.phoenixcontact.com/us/products/0830697>

Cycles	2
--------	---

## Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

## Ambient conditions

Ambient temperature (operation)	-40 °C ... 150 °C
Ambient temperature (storage/transport)	23 °C
Permissible humidity (storage/transport)	50 %
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	2 years

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

## Mounting

Mounting type	adhesive
---------------	----------

# WML 36 (25X38)A4 - Cable marker label



0830697

<https://www.phoenixcontact.com/us/products/0830697>

## Classifications

### ECLASS

ECLASS-11.0	27281102
ECLASS-12.0	27281102
ECLASS-13.0	27281102

### ETIM

ETIM 9.0	EC001530
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)