WML-FLAGV 6 (20X10)R CUS - Cable marking flags



0830717

https://www.phoenixcontact.com/us/products/0830717

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable marking flags, can be ordered: by line, white, labeled according to customer specifications, mounting type: adhesive, cable diameter: ≤ 6 mm, lettering field size: 20 x 10 mm

Your advantages

- · Self-adhesive conductor marking as a flag
- · High-quality marking created by the thermal transfer printer
- · Resistant to solvents
- · Can be printed on both sides

Commercial data

Item number	0830717
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8121
Catalog page	Page 199 (C-5-2013)
GTIN	4046356724616
Weight per piece (including packing)	0.588 g
Weight per piece (excluding packing)	0.588 g
Country of origin	PL

WML-FLAGV 6 (20X10)R CUS - Cable marking flags



0830717

https://www.phoenixcontact.com/us/products/0830717

Technical data

Product properties

Product type	Labeled conductor marker
Туре	Label
Marking	
Number of individual labels per row	3
Identification technology	Thermal transfer for rolls
ounting	
Mounting type	adhesive
aterial specifications	
Color	white
Material	Polyolefine
Base element material	Vinyl film
Components	free from silicone and halogen
Components	free from silicone and halogen
nvironmental and real-life conditions	free from silicone and halogen -40 °C 60 °C
nvironmental and real-life conditions	
nvironmental and real-life conditions Ambient conditions Ambient temperature (operation)	
nvironmental and real-life conditions Ambient conditions Ambient temperature (operation)	-40 °C 60 °C
Ambient conditions Ambient conditions Ambient temperature (operation) mensions Width	-40 °C 60 °C 10 mm
Ambient conditions Ambient conditions Ambient temperature (operation)	-40 °C 60 °C 10 mm
Ambient conditions Ambient conditions Ambient temperature (operation) mensions Width Length External dimensions	-40 °C 60 °C 10 mm 20 mm

WML-FLAGV 6 (20X10)R CUS - Cable marking flags



0830717

https://www.phoenixcontact.com/us/products/0830717

Classifications

ECLASS

ECLASS-12.0 27281102	ECLASS-11.0	27281102
	ECLASS-12.0	27281102
ECLASS-13.0 27281102	ECLASS-13.0	27281102

ETIM

	ETIM 9.0	EC001530	
UNSPSC			
	UNSPSC 21.0	39131500	





0830717

https://www.phoenixcontact.com/us/products/0830717

Environmental product compliance

REACh SVHC

4-(1,1,3,3-tetramethylbutyl)phenol, ethoxylated

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com