

US-TML (104X3,8) - Marker for terminal blocks



0830768

<https://www.phoenixcontact.com/us/products/0830768>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Marker for terminal blocks, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 104 x 3.8 mm, Number of individual labels: 22



Your advantages

- UniSheet marker strips, self-adhesive, for terminal blocks without marker groove
- The perforated marking strips are easy to separate and can be easily fitted

Commercial data

Item number	0830768
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BG09
Product key	BG2119
Catalog page	Page 139 (C-3-2019)
GTIN	4046356752565
Weight per piece (including packing)	5.698 g
Weight per piece (excluding packing)	4.84 g
Customs tariff number	39199080
Country of origin	DE

US-TML (104X3,8) - Marker for terminal blocks



0830768

<https://www.phoenixcontact.com/us/products/0830768>

Technical data

Product properties

Product type	Terminal marking
Type	Label

Marking

Number of individual labels	22
Number of individual labels per row	1
Identification technology	Thermal transfer for sheets and cards, UV LED technology

Dimensions

Width	3.8 mm
Length	104 mm

Material specifications

RoHS compliant	yes
Adhesive	Acrylic
Color	white
Material	Polyester
Components	free from silicone and halogen

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

US-TML (104X3,8) - Marker for terminal blocks



0830768

<https://www.phoenixcontact.com/us/products/0830768>

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-40 °C ... 150 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	2 years

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	adhesive
---------------	----------

US-TML (104X3,8) - Marker for terminal blocks



0830768

<https://www.phoenixcontact.com/us/products/0830768>

Classifications

ECLASS

ECLASS-11.0	27281101
ECLASS-12.0	27281101
ECLASS-13.0	27281101

ETIM

ETIM 9.0	EC000761
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com