

# WMTB-AL (D30) CUS - Aluminum label



0830806

<https://www.phoenixcontact.com/us/products/0830806>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Aluminum label, can be ordered: Piece, aluminum color, labeled according to customer specifications, mounting type: Assembly with cable ties, cable diameter: > 2.4 mm, lettering field size: d: 30 mm



## Product description

Note:  
Due to the current challenges of the global procurement market, Phoenix Contact has unfortunately been forced to accept an aluminum alloy material quality that may cause the appearance to deviate from the homogenous surface quality that was previously expected. This has no impact on the quality of the aluminum labels themselves or the durability of the printing. The effect is purely visual.

## Your advantages

- Aluminum cable marking for assembly with cable ties
- High-quality appearance
- Suitable for large-surface marking of wires and cables, > 2.4 mm in diameter

## Commercial data

Item number	0830806
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG813B
Catalog page	Page 161 (C-5-2013)
GTIN	4046356780827
Weight per piece (including packing)	1.872 g
Weight per piece (excluding packing)	1.51 g
Country of origin	PL

# WMTB-AL (D30) CUS - Aluminum label



0830806

<https://www.phoenixcontact.com/us/products/0830806>

## Technical data

### Product properties

Product type	Labeled conductor marker
--------------	--------------------------

### Marking

Identification technology	UV LED technology
---------------------------	-------------------

### Mounting

Mounting type	Assembly with cable ties
---------------	--------------------------

### Material specifications

Color	aluminum color
Material	Aluminum
Components	free from silicone, halogen, and cadmium

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

#### Ambient conditions

Recommended storage conditions	5 °C ... 25 °C
Recommended ambient temperature (storage/transport)	4 °C ... 25 °C
Shelf life	2 years

### Dimensions

Width	30 mm
Length	30 mm
Min. material thickness	0.80 mm

#### External dimensions

Outside diameter	2.4 mm ... 136 mm
------------------	-------------------

### Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

# WMTB-AL (D30) CUS - Aluminum label



0830806

<https://www.phoenixcontact.com/us/products/0830806>

## Classifications

### ECLASS

ECLASS-11.0	27281102
ECLASS-12.0	27281102
ECLASS-13.0	27281102

### ETIM

ETIM 9.0	EC001530
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)