# PMST (9X38) BN - Insert label

0830968

https://www.phoenixcontact.com/us/products/0830968

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Insert label, brown, pre-printed, mounting type: snapped, lettering field size: 9 x 38 mm, Number of individual labels: 1

## Your advantages

- The medium marking label is used in conjunction with insertable UCT-PMP ... labels in the CARRIER-PMP
- They are used to clearly identify devices and control cabinets
- They are secured in the CARRIER-PMP using rivets

## Commercial data

| Item number | 0830968 |
|---|---|
| Packing unit | 100 pc |
| Minimum order quantity | 100 pc |
| Product key | BG261Z |
| Catalog page | Page 317 (C-5-2015) |
| GTIN | 4046356912426 |
| Weight per piece (including packing) | 0.524 g |
| Weight per piece (excluding packing) | 0.47 g |
| Country of origin | DE |

## Technical data

### Product properties

| | |
|---|---|
| Product type | Labeled systems marker |
| Area of application | Identification of flow substances according to DIN 2403 |
| | Identification of flow substances according to DIN 2403 |

#### Marking

| | |
|---|---|
| Number of individual labels | 1 |
| Number of individual labels per row | 1 |

### Dimensions

| | |
|---|---|
| Width | 9 mm |
| Length | 38 mm |

### Material specifications

| | |
|---|---|
| Color | brown |
| Material | PVC |
| Flammability rating according to UL 94 | V0 |
| Components | Silicone-free |

### Environmental and real-life conditions

#### UV resistance

| | |
|---|---|
| Specification | ISO 4892-2:2013-03 (following) |
| Result | Test passed |
| Test duration | 96 h |

#### Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -30 °C ... 80 °C |
| Recommended ambient temperature (storage/transport) | 10 °C ... 30 °C |
| Recommended humidity (storage/transport) | 40 % ... 70 % (Storage in a dry and dark place in the original packaging is recommended) |
| Shelf life | 12 months |

### Standards and regulations

| | |
|---|---|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |

### Mounting

| | |
|---|---|
| Mounting type | snapped |

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-11.0 | 27281104 |
| ECLASS-12.0 | 27281104 |
| ECLASS-13.0 | 27281104 |

### ETIM

| | |
|---|---|
| ETIM 9.0 | EC001288 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39131500 |

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com