

LS-WMTB-AL (D25) BK CUS - Cable marker



0831798

<https://www.phoenixcontact.com/us/products/0831798>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Cable marker, Aluminum label, can be ordered: Piece, black, labeled according to customer specifications, mounting type: Assembly with cable ties, cable diameter: > 2.9 mm, lettering field size: d: 25 mm, Number of individual labels: 30



Your advantages

- Aluminum cable marking for assembly with cable ties
- Suitable for large-surface marking of wires and cables, > 2.9 mm in diameter
- Identification made from metal, high strength in a lightweight design
- Increased durability due to the decoratively anodized surface

Commercial data

Item number	0831798
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG813D
Catalog page	Page 249 (NTK-2014)
GTIN	4046356930093
Weight per piece (including packing)	99.99 g
Weight per piece (excluding packing)	99.99 g
Country of origin	PL

LS-WMTB-AL (D25) BK CUS - Cable marker



0831798

<https://www.phoenixcontact.com/us/products/0831798>

Technical data

Product properties

Product type	Labeled conductor marker
Type	Card form

Marking

Number of individual labels	30
Identification technology	Direct laser marking

Mounting

Mounting type	Assembly with cable ties
---------------	--------------------------

Material specifications

RoHS compliant	yes
Color	black
Material	Aluminum
Components	free from silicone, halogen, and cadmium

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-25 °C ... 70 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

Dimensions

Width	25 mm
Length	25 mm
Hole diameter	5.30 mm
Material strength	0.80 mm

External dimensions

Outside diameter	1 mm ... 136 mm
------------------	-----------------

Standards and regulations

LS-WMTB-AL (D25) BK CUS - Cable marker



0831798

<https://www.phoenixcontact.com/us/products/0831798>

Wipe resistance

DIN EN 61010-1 (VDE 0411-1)

LS-WMTB-AL (D25) BK CUS - Cable marker



0831798

<https://www.phoenixcontact.com/us/products/0831798>

Classifications

ECLASS

ECLASS-11.0	27281102
ECLASS-12.0	27281102
ECLASS-13.0	27281102

ETIM

ETIM 9.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com