

EC-E1 6A - Electronic circuit breaker



0903028

<https://www.phoenixcontact.com/us/products/0903028>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Electronic circuit breaker, signal contact: 1 N/O contact, nominal current: 6 A



Your advantages

- Error-free short-circuit detection even across long cable paths with the electronics characteristic curve
- Active current limitation to improve the capacity of the upstream power supply
- Increased system transparency with integrated floating remote indication contact (N/O)

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 0903028 |
| Packing unit | 6 pc |
| Minimum order quantity | 6 pc |
| Sales key | CL04 |
| Product key | CLA131 |
| Catalog page | Page 386 (C-4-2019) |
| GTIN | 4046356328036 |
| Weight per piece (including packing) | 69 g |
| Weight per piece (excluding packing) | 68 g |
| Customs tariff number | 85362010 |
| Country of origin | DE |

EC-E1 6A - Electronic circuit breaker



0903028

<https://www.phoenixcontact.com/us/products/0903028>

Technical data

Notes

| | |
|---------|--|
| General | When mounted in rows without convection cooling, the nominal device current should only be led to a maximum of 80% due to the thermal effect during continuous operation (100% operating factor). Special precautionary measures must be taken in systems or machines, to prevent components from restarting (e.g., use of a safety PLC). Parallel connection of multiple circuit breakers is not permitted. |
|---------|--|

Product properties

| | |
|---------------------|----------------------------|
| Type | DIN rail module, one-piece |
| Product type | Device circuit breakers |
| Product family | EC-E |
| Number of positions | 1 |
| No. of channels | 1 |

Insulation characteristics

| | |
|---------------------|---|
| Degree of pollution | 2 |
|---------------------|---|

Electrical properties

| | |
|-----------------------------|---------------------------|
| Fuse type | Automatic device |
| Switching capacity I_{CN} | Active current limitation |
| Fuse | electronic |

General

| | |
|------------------------------------|---|
| Operating voltage | 24 V DC |
| | 18 V DC ... 32 V DC |
| Nominal current I_N | 6 A |
| Rated surge voltage | 0.5 kV |
| Tripping method | E (electronic) |
| Required backup fuse | not required, integrated failsafe element |
| Dielectric strength | max. 32 V DC (Load circuit) |
| Switch off | Typ. $1.8 \times I_N$ |
| Active current limitation | active |
| Fuse | electronic |
| Closed-circuit current range I_0 | typ. 25 mA \pm 5 mA (When switched on) |
| MTBF (IEC 61709, SN 29500) | 7430000 h (at 25 °C with 80 % load) |
| | 6590000 h (at 40 °C with 80 % load) |
| Voltage drop | 130 mV (at I_N) |

Load circuit

| | |
|----------------------|---------------|
| Max. capacitive load | 20000 μ F |
|----------------------|---------------|

Auxiliary contact

EC-E1 6A - Electronic circuit breaker



0903028

<https://www.phoenixcontact.com/us/products/0903028>

| | |
|---|-------------------------|
| Contact connection type | floating signal contact |
| Minimum operating voltage U_{\min} DC | 10 V DC |
| Maximum operating voltage U_{\max} DC | 30 V DC |
| Minimum operating current I_{\min} | 10 mA |
| Max. operating current I_{\max} | 0.5 A |

Indicator/remote signaling

| | |
|--------------------|-------------------|
| Connection name | Auxiliary contact |
| Switching function | N/O contact |

Connection data

| | |
|-----------------------|-----------------------|
| Nominal cross section | 16.00 mm ² |
|-----------------------|-----------------------|

Line+ / LOAD+ /0V

| | |
|---|---|
| Screw thread | M4 |
| Tightening torque | ... 1.2 Nm |
| Stripping length | 10 mm |
| Conductor cross section rigid | 0.5 mm ² ... 16 mm ² |
| Cross section AWG | 20 ... 6 (converted acc. to IEC) |
| Conductor cross section flexible | 0.5 mm ² ... 16 mm ² |
| Conductor cross section, flexible [AWG] | 20 ... 6 (converted acc. to IEC) |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.5 mm ² ... 10 mm ² |
| Flexible conductor cross section (ferrule with plastic sleeve) | 0.5 mm ² ... 10 mm ² |
| 2 conductors with same cross section, solid | 0.5 mm ² ... 4 mm ² |
| 2 conductors with the same cross-section AWG rigid | 20 ... 12 (converted acc. to IEC) |
| 2 conductors with same cross section, flexible | 0.5 mm ² ... 4 mm ² |
| 2 conductors with the same cross-section AWG flexible | 20 ... 12 (converted acc. to IEC) |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve | 0.5 mm ² ... 2.5 mm ² |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm ² ... 6 mm ² |
| Nominal cross section | 16 mm ² |

Auxiliary contact

| | |
|---|--|
| Screw thread | M3 |
| Tightening torque | ... 0.5 Nm |
| Stripping length | 8 mm |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.25 mm ² ... 2.5 mm ² |
| Flexible conductor cross section (ferrule with plastic sleeve) | 0.25 mm ² ... 2.5 mm ² |

Line+/LOAD+/0V

| | |
|----------------------------------|--|
| Connection method | Screw connection |
| Screw thread | M4 |
| Tightening torque | 1.2 Nm |
| Stripping length | 10 mm |
| Conductor cross section flexible | 0.5 mm ² ... 16 mm ² |

EC-E1 6A - Electronic circuit breaker



0903028

<https://www.phoenixcontact.com/us/products/0903028>

| | |
|---|--|
| Conductor cross section rigid | 0.5 mm ² ... 16 mm ² |
| Conductor cross section AWG | 20 ... 6 |
| Conductor cross section, flexible, with ferrule, with plastic sleeve | 0.5 mm ² ... 10 mm ² |
| Conductor cross section flexible, with ferrule without plastic sleeve | 0.5 mm ² ... 10 mm ² |

Auxiliary contact

| | |
|---|--|
| Connection method | Screw connection |
| Screw thread | M3 |
| Tightening torque | 0.5 Nm |
| Stripping length | 8 mm |
| Conductor cross section AWG | 24 ... 14 |
| Conductor cross section, flexible, with ferrule, with plastic sleeve | 0.25 mm ² ... 2.5 mm ² |
| Conductor cross section flexible, with ferrule without plastic sleeve | 0.25 mm ² ... 2.5 mm ² |

Dimensions

| | |
|------------------|---------|
| Width | 12.5 mm |
| Height | 83 mm |
| Height NS 35/15 | 90.5 mm |
| Height NS 35/7,5 | 83 mm |
| Depth | 80 mm |

Material specifications

| | |
|--|------------------|
| Color | black (RAL 9005) |
| Flammability rating according to UL 94 | V0 |

Environmental and real-life conditions

Ambient conditions

| | |
|---|---------------------------------|
| Degree of protection | IP20 (Housing) |
| Ambient temperature (operation) | 0 °C ... 50 °C (non-condensing) |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Humidity test | 96 h, 95 % RH, 40 °C |

Standards and regulations

| | |
|--------------------------|----------|
| Standards/specifications | UL 508 |
| Standards/specifications | CSA 22.2 |
| Note | No. 14 |
| Standards/specifications | UL 2367 |
| Standards/specifications | CSA 22.2 |
| Note | No. 142 |
| Standards/specifications | CSA 22.2 |
| Note | No. 213 |
| Standards/specifications | UL 1604 |

EC-E1 6A - Electronic circuit breaker



0903028

<https://www.phoenixcontact.com/us/products/0903028>

Mounting

| Mounting type |
|---------------|
|---------------|

| |
|-----------------|
| DIN rail: 35 mm |
|-----------------|

EC-E1 6A - Electronic circuit breaker



0903028

<https://www.phoenixcontact.com/us/products/0903028>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27140401 |
| ECLASS-12.0 | 27140401 |
| ECLASS-13.0 | 27140401 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC003538 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

EC-E1 6A - Electronic circuit breaker



0903028

<https://www.phoenixcontact.com/us/products/0903028>

Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 25; |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com