

Fuse insert - S 2 A/380 V - 0913016

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fuse insert, nominal current: 2 A, length: 36 mm, diameter: 11 mm, color: pink

Your advantages

- ✓ Contains no lead, cadmium, chromium 6 (ROHS-compliant)
- ✓ Safe shutoff of impermissible overcurrents and short-circuit currents up to the nominal shutoff current
- ✓ NEOZED® fuse-links with gG characteristic for protecting lines and equipment
- ✓ Colored indicating pins on the butt contact show the operating state



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 017918 008116
GTIN	4017918008116
Weight per Piece (excluding packing)	6.080 g
Custom tariff number	85361010
Country of origin	Hungary

Technical data

General

Color	pink
Maximum power dissipation for nominal condition	2.5 W

Dimensions

Length	36 mm
--------	-------

Fuse insert - S 2 A/380 V - 0913016

Technical data

Dimensions

Diameter	11 mm
----------	-------

General

Nominal current I_N	2 A
Nominal voltage U_N	400 V AC (250 V DC)
Fuse	gL/gK NEOZED

Ambient conditions

Operating temperature	-60 °C ... 85 °C
Ambient temperature (storage/transport)	-25 °C ... 55 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Permissible humidity (storage/transport)	30 % ... 70 %
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27142002
eCl@ss 11.0	27142002
eCl@ss 4.0	27142000
eCl@ss 4.1	27142000
eCl@ss 5.0	27142000
eCl@ss 5.1	27142000
eCl@ss 6.0	27142000
eCl@ss 7.0	27142002
eCl@ss 9.0	27142002

ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC000899
ETIM 4.0	EC000899
ETIM 6.0	EC002704
ETIM 7.0	EC002704

Fuse insert - S 2 A/380 V - 0913016

Classifications

UNSPSC

UNSPSC 6.01	30211813
UNSPSC 7.0901	39121410
UNSPSC 11	39121412
UNSPSC 12.01	39121412
UNSPSC 13.2	39121627
UNSPSC 18.0	39121627
UNSPSC 19.0	39121627
UNSPSC 20.0	39121627
UNSPSC 21.0	39121627