

Fuse insert - S 4 A/380 V - 0913029

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fuse insert, nominal current: 4 A, length: 36 mm, diameter: 11 mm, color: brown

Your advantages

- ✓ Contains no lead, cadmium, chromium 6 (ROHS-compliant)
- ✓ Colored indicating pins on the butt contact show the operating state
- ✓ NEOZED® fuse-links with gG characteristic for protecting lines and equipment
- ✓ Safe shutoff of impermissible overcurrents and short-circuit currents up to the nominal shutoff current



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| GTIN |  4 017918 008123 |
| GTIN | 4017918008123 |
| Weight per Piece (excluding packing) | 6.240 g |
| Custom tariff number | 85361010 |
| Country of origin | Hungary |

Technical data

General

| | |
|---|-------|
| Color | brown |
| Maximum power dissipation for nominal condition | 1.8 W |

Dimensions

| | |
|--------|-------|
| Length | 36 mm |
|--------|-------|

Fuse insert - S 4 A/380 V - 0913029

Technical data

Dimensions

| | |
|----------|-------|
| Diameter | 11 mm |
|----------|-------|

General

| | |
|--------------------------------|---------------------|
| Nominal current I _N | 4 A |
| Nominal voltage U _N | 400 V AC (250 V DC) |
| Fuse | gL/gK NEOZED |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27142002 |
| eCl@ss 11.0 | 27142002 |
| eCl@ss 4.0 | 27142000 |
| eCl@ss 4.1 | 27142000 |
| eCl@ss 5.0 | 27142000 |
| eCl@ss 5.1 | 27142000 |
| eCl@ss 6.0 | 27142000 |
| eCl@ss 7.0 | 27142002 |
| eCl@ss 9.0 | 27142002 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000899 |
| ETIM 3.0 | EC000899 |
| ETIM 4.0 | EC000899 |
| ETIM 6.0 | EC002704 |
| ETIM 7.0 | EC002704 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211813 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121412 |
| UNSPSC 12.01 | 39121412 |
| UNSPSC 13.2 | 39121627 |
| UNSPSC 18.0 | 39121627 |
| UNSPSC 19.0 | 39121627 |
| UNSPSC 20.0 | 39121627 |
| UNSPSC 21.0 | 39121627 |

Fuse insert - S 4 A/380 V - 0913029

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|--------------------------|
| EAC |  | RU C- DE.BL08.B.00724 |
|-----|---|--------------------------|
