

Fuse insert - S-II-10 A/500 V - 0913634

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fuse insert, nominal current: 10 A, length: 50 mm, diameter: 22 mm, color: red

Your advantages

- ✓ Colored indicating pins on the butt contact show the operating state
- ✓ Safe shutoff of impermissible overcurrents and short-circuit currents up to the nominal shutoff current
- ✓ DIAZED® fuse-links with gG characteristic for protecting lines and equipment
- ✓ Contains no lead, cadmium, chromium 6 (ROHS-compliant)



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
GTIN	 4 017918 008604
GTIN	4017918008604
Weight per Piece (excluding packing)	27.840 g
Custom tariff number	85361010
Country of origin	Hungary

Technical data

General

Color	red
-------	-----

Dimensions

Length	50 mm
Diameter	22 mm

Fuse insert - S-II-10 A/500 V - 0913634

Technical data

General

Nominal current I_N	10 A
Nominal voltage U_N	500 V AC/DC
Fuse	gL/gG DIAZED

Ambient conditions

Operating temperature	-60 °C ... 85 °C
Ambient temperature (storage/transport)	-25 °C ... 55 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Permissible humidity (storage/transport)	30 % ... 70 %
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C

Classifications

eCl@ss

eCl@ss 10.0.1	27142004
eCl@ss 11.0	27142004
eCl@ss 4.0	27142000
eCl@ss 4.1	27142000
eCl@ss 5.0	27142000
eCl@ss 5.1	27142000
eCl@ss 6.0	27142000
eCl@ss 7.0	27142002
eCl@ss 9.0	27142004

ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC000899
ETIM 4.0	EC000899
ETIM 6.0	EC002704
ETIM 7.0	EC002704

UNSPSC

UNSPSC 6.01	30211813
UNSPSC 7.0901	39121410
UNSPSC 11	39121412
UNSPSC 12.01	39121412
UNSPSC 13.2	39121627
UNSPSC 18.0	39121627

Fuse insert - S-II-10 A/500 V - 0913634

Classifications

UNSPSC

UNSPSC 19.0	39121627
UNSPSC 20.0	39121627
UNSPSC 21.0	39121627

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.BL08.B.00724
-----	---	--------------------------
