

0914196

https://www.phoenixcontact.com/us/products/0914196

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Thermal-magnetic circuit breaker, 1-pos., fast blow, 1 N/C contact, with universal foot for mounting on NS 32 or NS 35 $\,$

Commercial data

Item number	0914196
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	CL04
Product key	CLA121
Catalog page	Page 282 (CL-2002)
GTIN	4017918008871
Weight per piece (including packing)	68.85 g
Weight per piece (excluding packing)	68.15 g
Customs tariff number	85362010
Country of origin	DE



0914196

https://www.phoenixcontact.com/us/products/0914196

Technical data

Product properties

Туре	DIN rail module, one-piece	
Product type	Thermomagnetic device circuit breakers	
Product family	TMC	
Number of positions	1	
Number of connections	4	
Number of rows	2	
No. of channels	1	
Insulation characteristics		
Overvoltage category	II	
Degree of pollution	2	

Automatic device

Auxiliary contact 250 V AC

0.2 A AC (Low-induction)

65 V DC

Electrical properties

Fuse type

ted voltage	65 V DC
Rated current I _N	0.2 A
Rated surge voltage	2.5 kV
nsulation resistance R _{iso}	> 100 MΩ (500 V DC)
Auxiliary circuit	240 V AC / 1 A (Low-induction)
	65 V AC / 1 A (Low-induction)
Tripping method	TM (thermomagnetic)
Device resistance	39.3 Ω
Rated short-circuit switching capacity I _{cn}	2500 A (32 V DC)
Short-circuit switching capacity	2000 A (UL 1077: 65 V DC)
Dielectric strength	3000 V AC (Actuation area)
	3000 V AC (Main to auxiliary circuit)
Switching cycles, max.	10000 (At 1 x I _n , inductive)
Fuse	F1 (fast blow)

Connection data

Connection name

Operating voltage

Operating current

Main contact

man contact	
Screw thread	M3
Tightening torque	0.6 0.8 Nm



0914196

https://www.phoenixcontact.com/us/products/0914196

Stripping length	12 mm
Internal cylindrical gage	A3
Conductor cross section rigid	0.2 mm² 6 mm²
Cross section AWG	24 10 (converted acc. to IEC)
Conductor cross section flexible	0.2 mm² 4 mm²
Conductor cross-section flexible (ferrule without plastic sleeve)	0.25 mm² 4 mm²
Flexible conductor cross section (ferrule with plastic sleeve)	0.25 mm² 2.5 mm²
2 conductors with same cross section, solid	0.2 mm² 0.75 mm²
2 conductors with same cross section, flexible	0.2 mm² 0.75 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.25 mm² 1 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm² 2.5 mm²
Nominal current	0.2 A
A. War and the f	
Auxiliary contact	M2
Screw thread	M3
Tightening torque	0.6 0.8 Nm
Stripping length	12 mm
Internal cylindrical gage	A1 0.2 mm² 2.5 mm²
Conductor cross section rigid	
Cross section AWG	24 14 (converted acc. to IEC)
Conductor cross section flexible	0.2 mm² 1.5 mm²
Conductor cross-section flexible (ferrule without plastic sleeve)	0.25 mm² 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve)	0.25 mm² 1.5 mm²
2 conductors with same cross section, solid	0.2 m ² 0.75 m ²
2 conductors with same cross section, flexible	0.2 m ² 0.75 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.25 mm² 0.5 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm² 0.75 mm²
Main contact	
Connection method	Screw connection
Screw thread	M3
Tightening torque	0.6 Nm 0.8 Nm
Stripping length	12 mm
Conductor cross section flexible	0.2 mm² 4 mm²
Conductor cross section rigid	0.2 mm² 6 mm²
Conductor cross section AWG	24 10
Conductor cross section, flexible, with ferrule, with plastic sleeve	0.25 mm² 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve	0.25 mm² 4 mm²
Auxiliary contact	
Connection method	Screw connection
Screw thread	M3




0914196

https://www.phoenixcontact.com/us/products/0914196

Tightening torque	0.6 Nm 0.8 Nm
Stripping length	12 mm
Conductor cross section flexible	0.2 mm² 1.5 mm²
Conductor cross section rigid	0.2 mm² 2.5 mm²
Conductor cross section AWG	24 14
Conductor cross section, flexible, with ferrule, with plastic sleeve	0.25 mm² 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve	0.25 mm² 2.5 mm²

Dimensions



Material specifications

Color	black (RAL 9005)
Flammability rating according to UL 94	V-2
Insulating material group	II
Insulating material	PA66

Mechanical properties

Mechanical data

Open side panel	No

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP30 (Actuation area)
	IP20 (Connection area)
Ambient temperature (operation)	-30 °C 60 °C
Humidity test	240 h, 95 % RH, 40 °C

Standards and regulations

Standards/specifications	EN 60934
Standards/specifications	UL 1077

Mounting

Mounting type	DIN rail: 35 mm



0914196

https://www.phoenixcontact.com/us/products/0914196

Classifications

ECLASS

	ECLASS-11.0	27141116		
	ECLASS-12.0	27141116		
	ECLASS-13.0	27140401		
ETIM				
	ETIM 9.0	EC000899		
UNSPSC				
	UNSPSC 21.0	39121400		



0914196

https://www.phoenixcontact.com/us/products/0914196

Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 25;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com