

PABA WH/10 - Insert label



1013753

<https://www.phoenixcontact.com/us/products/1013753>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Insert label, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 20

Commercial data

| | |
|--------------------------------------|--------------------|
| Item number | 1013753 |
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| Sales key | BG20 |
| Product key | BG2213 |
| Catalog page | Page 421 (CL-2005) |
| GTIN | 4017918013943 |
| Weight per piece (including packing) | 5.754 g |
| Weight per piece (excluding packing) | 3.84 g |
| Customs tariff number | 39269097 |
| Country of origin | CN |

Technical data

Notes

| | |
|---------|-------------------------|
| General | Can be labeled with CMS |
|---------|-------------------------|

Product properties

| | |
|--------------|-------------------|
| Product type | Conductor marking |
|--------------|-------------------|

Marking

| | |
|-------------------------------------|----|
| Number of individual labels | 20 |
| Number of individual labels per row | 1 |

Dimensions

| | |
|--------|-------|
| Width | 10 mm |
| Length | 4 mm |

Material specifications

| | |
|--|-------|
| Color | white |
| Material | ABS |
| Flammability rating according to UL 94 | V0 |

Cable/line

| | |
|-------------------------|-----------------|
| External cable diameter | 0.6 mm ... 7 mm |
|-------------------------|-----------------|

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

| | |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

Scratch test for the determining scratch resistance

| | |
|---------------|---------------------------------------|
| Specification | DIN EN ISO 1518-1:2019-10 (following) |
| Requirements | ≥ 5 N |
| Result | Test passed |

Tesafilm test

| | |
|---------------|----------------------------------|
| Specification | DIN EN ISO 2409:2013 (following) |
| Result | Test passed |

UV resistance

| | |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
| Result | Test passed |
| Test duration | 96 h |

Temperature resistance

| | |
|-----------------------|---------------------------------|
| Specification | ANSI/UL 969-2018:03 (following) |
| Test duration | 240 h |
| Rating 80 °C (105 °C) | Test passed |

PABA WH/10 - Insert label



1013753

<https://www.phoenixcontact.com/us/products/1013753>

| | |
|---|--------------------------|
| Specification | ISO 175:2010 (following) |
| Test duration | 168 h |
| Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2] | Test passed |
| Ethanol (99 %) [CAS No. 64-17-5] | Test passed |
| Diesel [CAS No. 68476-34-6] | Test passed |
| IRM 901 | Test passed |
| IRM 902 | Test passed |

Testing in a condensation changing climate in the presence of sulfur dioxide

| | |
|---------------|-------------------|
| Specification | DIN 50018:2013-05 |
| Result | Test passed |
| Climate level | AHT 1.0 S |
| Cycles | 2 |

Salt spray test

| | |
|---------------|---------------------------|
| Specification | DIN EN 60068-2-11:2000-02 |
| Result | Test passed |
| Test duration | 96 h |

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -15 °C ... 65 °C |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % (Storage in a dry and dark place in the original packaging is recommended) |

Standards and regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

Mounting

| | |
|---------------|----------|
| Mounting type | slide-on |
|---------------|----------|

PABA WH/10 - Insert label



1013753

<https://www.phoenixcontact.com/us/products/1013753>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27281102 |
| ECLASS-12.0 | 27281102 |
| ECLASS-13.0 | 27281102 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001530 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com