

PML-M112 (D200) - Mandatory sign

1014172

<https://www.phoenixcontact.com/us/products/1014172>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Mandatory sign, Sheet, blue/white, labeled: Wear head cover, mounting type: adhesive, diameter: 200 mm, lettering field size: Ø 200 mm, Number of individual labels: 1

Your advantages

- Stick-on mandatory signs, preprinted, with symbol
- The mandatory signs conform to the ISO 7010 international standard
- Suitable for indoor and outdoor use
- Highly flexible, soft PVC label that adapts well to uneven surfaces

Commercial data

Item number	1014172
Packing unit	5 pc
Minimum order quantity	1 pc
Product key	BG2624
Catalog page	Page 341 (C-5-2015)
GTIN	4046356784177
Weight per piece (including packing)	20.35 g
Weight per piece (excluding packing)	20.35 g
Country of origin	DE

PML-M112 (D200) - Mandatory sign



1014172

<https://www.phoenixcontact.com/us/products/1014172>

Technical data

Product properties

Type	circular
Product type	Mandatory sign printed
Area of application	Mandatory signs
	Mandatory marking according to ISO 7010

Marking

Number of individual labels	1
Printing	Wear head cover

Dimensions

Width	0 mm
Height	0 mm
Diameter	200.00 mm

Material specifications

Color	blue/white
Material	PVC
Components	Silicone-free

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N
Result	Test passed

Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

UV resistance

Specification	DIN EN ISO 4892-2:2021-11 (following)
Result	Test passed
Test duration	96 h
Specification	IEC 60068-2-2:2007-07
Result	Test passed
Duration	96 h
Temperature for testing	120 °C

Temperature resistance

PML-M112 (D200) - Mandatory sign



1014172

<https://www.phoenixcontact.com/us/products/1014172>

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 100 °C (121 °C)	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h
Diesel [CAS No. 68476-34-6]	Test passed
IRM 901	Test passed
IRM 902	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-40 °C ... 90 °C
Ambient temperature (assembly)	> 10 °C
Recommended ambient temperature (storage/transport)	22 °C
Recommended humidity (storage/transport)	50 % ... 55 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	2 years

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	adhesive
---------------	----------

PML-M112 (D200) - Mandatory sign



1014172

<https://www.phoenixcontact.com/us/products/1014172>

Classifications

ECLASS

ECLASS-11.0	40200201
ECLASS-12.0	40200201
ECLASS-13.0	40200201

ETIM

ETIM 9.0	EC001777
----------	----------

UNSPSC

UNSPSC 21.0	55121700
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com