US-PML-P200 (D50) CUS - Prohibition sign



1014223

https://www.phoenixcontact.com/us/products/1014223

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Prohibition sign, can be ordered: by card, white, labeled according to customer specifications: Blank, mounting type: adhesive, diameter: 50 mm, lettering field size: Ø: 50 mm, Number of individual labels: 4



Your advantages

· UniSheet - stick-on prohibition sign, unprinted

Commercial data

| Item number | 1014223 |
|--------------------------------------|--------------------------------|
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Product key | BG8159 |
| Catalog page | Page 326 (C-5-2013) |
| GTIN | 4046356786782 |
| Weight per piece (including packing) | 5.29 g |
| Weight per piece (excluding packing) | 5.29 g |
| Country of origin | PL |

US-PML-P200 (D50) CUS - Prohibition sign



1014223

https://www.phoenixcontact.com/us/products/1014223

Technical data

Product properties

| Prohibition sign printed | | |
|---|--|--|
| D 17177 | | |
| Prohibition marking according to ISO 7010 | | |
| Marking | | |
| 4 | | |
| Blank | | |
| _ | | |

Dimensions

| Width | 0 mm |
|-------------------------|----------|
| Height | 0 mm |
| Depth | 0.09 mm |
| Diameter | 50.00 mm |
| Min. material thickness | 0.09 mm |

Material specifications

| Color | white |
|------------|---------------|
| Material | PVC |
| Components | Silicone-free |

Environmental and real-life conditions

Ambient conditions

| Ambient temperature (operation) | -40 °C 100 °C |
|---|--|
| Ambient temperature (assembly) | > 10 °C |
| Recommended ambient temperature (storage/transport) | 22 °C |
| Recommended humidity (storage/transport) | 50 % 55 % (Storage in a dry and dark place in the original packaging is recommended) |
| Shelf life | 2 years |

Standards and regulations

| | Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|---|-----------------|-----------------------------|
| М | ounting | |
| | Mounting type | adhesive |

US-PML-P200 (D50) CUS - Prohibition sign



1014223

https://www.phoenixcontact.com/us/products/1014223

Classifications

ECLASS

| | ECLASS-11.0 | 40200202 | |
|--------|-------------|----------|--|
| | ECLASS-12.0 | 40200202 | |
| | ECLASS-13.0 | 40200202 | |
| ETIM | | | |
| | ETIM 9.0 | EC001777 | |
| UNSPSC | | | |
| | UNSPSC 21.0 | 55121700 | |

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com