

# PML-P100 (D50)R - Prohibition sign



1014225

<https://www.phoenixcontact.com/us/products/1014225>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Prohibition sign, Roll, red/white, labeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, diameter: 50 mm, lettering field size: Ø: 50 mm, Number of individual labels: 500

## Your advantages

- The color preprinted PML-P ... prohibition signs without symbols allow you to create custom prohibition notices
- The label consists of soft, highly flexible PVC film that molds itself to uneven surfaces
- The prohibition signs conform to the ISO 7010 international standard
- When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences
- Marking service: Phoenix Contact can custom-mark all PLM-P ... markers according to your specifications

## Commercial data

Item number	1014225
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG21
Product key	BG2611
Catalog page	Page 372 (C-3-2019)
GTIN	4046356784771
Weight per piece (including packing)	390.1 g
Weight per piece (excluding packing)	390 g
Customs tariff number	39199080
Country of origin	DE

# PML-P100 (D50)R - Prohibition sign



1014225

<https://www.phoenixcontact.com/us/products/1014225>

## Technical data

### Product properties

Type	circular
Product type	Prohibition sign unprinted
Area of application	Prohibition signs
	Prohibition marking according to ISO 7010

### Marking

Number of individual labels	500
Number of individual labels per row	1

### Dimensions

Width	50 mm
Height	50 mm
Diameter	50.00 mm

### Material specifications

Color	red/white
Material	PVC
Components	Silicone-free

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 90 °C
Ambient temperature (assembly)	> 10 °C
Recommended ambient temperature (storage/transport)	22 °C
Recommended humidity (storage/transport)	50 % ... 55 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	2 years

### Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

### Mounting

Mounting type	adhesive
---------------	----------

# PML-P100 (D50)R - Prohibition sign



1014225

<https://www.phoenixcontact.com/us/products/1014225>

## Classifications

### ECLASS

ECLASS-11.0	40200202
ECLASS-12.0	40200202
ECLASS-13.0	40200202

### ETIM

ETIM 9.0	EC001777
----------	----------

### UNSPSC

UNSPSC 21.0	55121700
-------------	----------

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)