

PML-T102 (26X280)R - Pipeline markers



1014231

<https://www.phoenixcontact.com/us/products/1014231>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Pipeline markers, Roll, red, pre-printed, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2: pre-printed, mounting type: adhesive, diameter: 0 mm, lettering field size: 26 x 280 mm, Number of individual labels: 250

Your advantages

- Stick-on pipeline markers, unmarked
- Suitable for indoor and outdoor use
- Pipeline marking according to DIN 2403
- In combination with the PML-GHS hazardous substances labels, marking which conforms to the Ordinance on Hazardous Substances (GefStoffV) can be applied
- High adhesive strength
- Finely perforated arrowheads enable the arrowheads which are not required to be easily removed
- High temperature resistance
- Group 2 (steam)

Commercial data

Item number	1014231
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG21
Product key	BG2611
Catalog page	Page 379 (C-3-2019)
GTIN	4046356784276
Weight per piece (including packing)	491.11 g
Weight per piece (excluding packing)	491.11 g
Customs tariff number	39199080
Country of origin	DE

PML-T102 (26X280)R - Pipeline markers



1014231

<https://www.phoenixcontact.com/us/products/1014231>

Technical data

Product properties

Type	Rectangle
Product type	System marking
Area of application	Pipeline labels
	Pipeline identification according to DIN 2403

Marking

Number of individual labels	250
Printing	pre-printed

Dimensions

Width	280 mm
Height	26 mm
Length	26 mm
Diameter	0.00 mm

Material specifications

RoHS compliant	yes
Foil strength	50 µm
Adhesive	Acrylic
Color	red
Material	Polyester

Environmental and real-life conditions

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S

PML-T102 (26X280)R - Pipeline markers



1014231

<https://www.phoenixcontact.com/us/products/1014231>

Cycles	2
--------	---

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-40 °C ... 150 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Shelf life	2 years

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	adhesive
---------------	----------

PML-T102 (26X280)R - Pipeline markers



1014231

<https://www.phoenixcontact.com/us/products/1014231>

Classifications

ECLASS

ECLASS-11.0	40200202
ECLASS-12.0	40200202
ECLASS-13.0	40200202

ETIM

ETIM 9.0	EC001777
----------	----------

UNSPSC

UNSPSC 21.0	55121700
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com