

PML-T101 (26X280)R CUS - Pipeline markers



1014249

<https://www.phoenixcontact.com/us/products/1014249>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Pipeline markers, can be ordered: by line, green, labeled according to customer specifications:
Water, mounting type: adhesive, diameter: 0 mm, lettering field size: 26 x 280 mm

Your advantages

- Stick-on pipeline markers, unmarked
- Suitable for indoor and outdoor use
- Pipeline marking according to DIN 2403
- In combination with the PML-GHS hazardous substances labels, marking which conforms to the Ordinance on Hazardous Substances (GefStoffV) can be applied
- High adhesive strength
- Finely perforated arrowheads enable the arrowheads which are not required to be easily removed
- High temperature resistance
- Group 1 (water)

Commercial data

Item number	1014249
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8151
Catalog page	Page 342 (C-5-2013)
GTIN	4046356784450
Weight per piece (including packing)	7.129 g
Weight per piece (excluding packing)	7.128 g
Country of origin	PL

PML-T101 (26X280)R CUS - Pipeline markers



1014249

<https://www.phoenixcontact.com/us/products/1014249>

Technical data

Product properties

Type	Rectangle
Product type	Labeled systems marker
Area of application	Pipeline labels
	Pipeline identification according to DIN 2403

Marking

Number of individual labels per row	3
Printing	Water

Dimensions

Width	280 mm
Height	26 mm
Length	26 mm
Diameter	0.00 mm

Material specifications

RoHS compliant	yes
Foil strength	50 µm
Adhesive	Acrylic
Color	green
Material	Polyester

Environmental and real-life conditions

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-40 °C ... 150 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Shelf life	2 years

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	adhesive
---------------	----------

PML-T101 (26X280)R CUS - Pipeline markers



1014249

<https://www.phoenixcontact.com/us/products/1014249>

Classifications

ECLASS

ECLASS-11.0	40200202
ECLASS-12.0	40200202
ECLASS-13.0	40200202

ETIM

ETIM 9.0	EC001777
----------	----------

UNSPSC

UNSPSC 21.0	55121700
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com