

PML-GHS100 (25X25)R - Hazardous substances label



1014290

<https://www.phoenixcontact.com/us/products/1014290>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Hazardous substances label, Roll, red/white, pre-printed, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, diameter: 0 mm, lettering field size: 25 x 25 mm, Number of individual labels: 500

Your advantages

- The color preprinted PML-GHS ... hazardous substance labels without symbols allow you to create custom hazard notices. A wide range of symbols are available in the PROJECT complete software.
- The markers conform to the GHS international standard
- When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences

Commercial data

Item number	1014290
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG21
Product key	BG2611
Catalog page	Page 374 (C-3-2019)
GTIN	4046356787055
Weight per piece (including packing)	172 g
Weight per piece (excluding packing)	172 g
Customs tariff number	39199080
Country of origin	DE

Technical data

Product properties

Type	Diamond
Product type	Warning label unprinted
Area of application	Hazardous substance labels
	Hazardous substance labeling according to CLP/GHS regulation

Marking

Number of individual labels	500
Number of individual labels per row	2

Dimensions

Width	25 mm
Height	25 mm
Length	25 mm
Diameter	0.00 mm

Material specifications

Color	red/white
Material	Polyester
Components	Silicone-free

Environmental and real-life conditions

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-40 °C ... 150 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	adhesive
---------------	----------

PML-GHS100 (25X25)R - Hazardous substances label



1014290

<https://www.phoenixcontact.com/us/products/1014290>

Classifications

ECLASS

ECLASS-11.0	40200202
ECLASS-13.0	40200202
ECLASS-12.0	40200202

ETIM

ETIM 9.0	EC001777
----------	----------

UNSPSC

UNSPSC 21.0	55121700
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com