

Replacement die - CRIMPFOX-M TC 4/DIE - 1212075

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Die, for Crimpfox-M, for turned contacts 0.5 ... 4 mm², packed in a serial storage box

Your advantages

- ✓ Marked die stations for precise processing of corresponding cross sections
- ✓ For CK 2,5 ED..., CK 4,0 ED... turned pin and socket contacts

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 452540
GTIN	4046356452540
Weight per Piece (excluding packing)	80.000 g
Custom tariff number	82032000
Country of origin	Sweden

Technical data

Dimensions

Length (b)	114 mm
Width (a)	75 mm
Height (c)	25.5 mm

General

Color	black
Compression	Square crimp
Type of contact	Turned contacts
Min. cross section	0.5 mm ²
Max. cross section	4 mm ²
AWG min	20
AWG max	12

Replacement die - CRIMPFOX-M TC 4/DIE - 1212075

Technical data

General

Weight	72 g
--------	------

Classifications

eCl@ss

eCl@ss 10.0.1	21019290
eCl@ss 11.0	21049090
eCl@ss 4.0	21040300
eCl@ss 4.1	21040300
eCl@ss 5.0	21040300
eCl@ss 5.1	21040300
eCl@ss 6.0	21043800
eCl@ss 7.0	21043811
eCl@ss 9.0	21019290

ETIM

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001282
ETIM 6.0	EC001282
ETIM 7.0	EC001282

UNSPSC

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518
UNSPSC 19.0	27111518

Approvals

Approvals

Approvals

EAC

Replacement die - CRIMPFOX-M TC 4/DIE - 1212075

Approvals

Ex Approvals

Approval details

EAC		RU x- DE..xx08.B.02974
-----	---	---------------------------