

TSD-M 3NM - Torque screwdriver



1212225

<https://www.phoenixcontact.com/us/products/1212225>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 1.2 - 3 Nm

Your advantages

- TSD-M... torque screwdrivers are easy to adjust to the required torque within the range of 1.2 Nm ... 3,0 Nm
- Torque screwdrivers with hexagonal fast connection holder
- High-precision, finely adjustable torque screwdrivers in accordance with EN ISO 6789

Commercial data

Item number	1212225
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BH31
Product key	BH314A
Catalog page	Page 453 (C-3-2019)
GTIN	4046356455565
Weight per piece (including packing)	190 g
Weight per piece (excluding packing)	179 g
Customs tariff number	82054000
Country of origin	CZ

TSD-M 3NM - Torque screwdriver



1212225

<https://www.phoenixcontact.com/us/products/1212225>

Technical data

Notes

Environmental Product Compliance	
California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration

Product properties

Product type	Torque tool
--------------	-------------

Connection data

Torque range	1.2 Nm ... 3 Nm 6 %
Output	External hexagonal

Dimensions

Width	36.5 mm
Blade width	0 mm
Height	36.5 mm
Length	150 mm
Blade thickness	0 mm

Material specifications

Color	black
-------	-------

TSD-M 3NM - Torque screwdriver



1212225

<https://www.phoenixcontact.com/us/products/1212225>

Classifications

ECLASS

ECLASS-11.0	21040417
ECLASS-12.0	21040417
ECLASS-13.0	21040417

ETIM

ETIM 9.0	EC011814
----------	----------

UNSPSC

UNSPSC 21.0	27111700
-------------	----------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com