TSD 25 SAC - Torque screwdriver



1212315

https://www.phoenixcontact.com/us/products/1212315

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Torque screwdriver, with preset torque of 2.5 Nm and 4 mm hexagonal drive for the pressure nut of the connector hood

Your advantages

- TSD ... SAC torque screwdrivers with a range of preset torques from 0.2 Nm to 2.5 Nm
- For the TSD-M... torque screwdrivers the torque can be set individually
- · The TSD-M... adapters can accommodate the various nuts
- · Wide range of SAC... nuts for various different applications

Commercial data

Item number	1212315
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BH31
Product key	BH314A
Catalog page	Page 460 (C-3-2019)
GTIN	4046356455596
Weight per piece (including packing)	101.4 g
Weight per piece (excluding packing)	100 g
Customs tariff number	82054000
Country of origin	CZ

TSD 25 SAC - Torque screwdriver



https://www.phoenixcontact.com/us/products/1212315



Technical data

Notes

ļ	Environmental Product Compliance		
	California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration	
Pr	oduct properties		
	Туре	Hexagonal SW4	
	Product type	Torque tool	

Connection data

Torque range	2.5 Nm 2.5 Nm
Output	External hexagonal

Dimensions

Width	37 mm
Blade width	0 mm
Blade height	100 mm
Length	205 mm
Blade thickness	0 mm

Material specifications

Color black

TSD 25 SAC - Torque screwdriver



1212315

https://www.phoenixcontact.com/us/products/1212315

Classifications

ECLASS

ECLASS-11.0	21040417			
ECLASS-12.0	21040417			
ECLASS-13.0	21040417			
ETIM				
ETIM 9.0	EC011814			
UNSPSC				
UNSPSC 21.0	27111700			

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com