SF-SL 0,6X3,5-200 - Screwdriver



https://www.phoenixcontact.com/us/products/1212550



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Screwdriver, slot-headed, size: 0.6 x 3.5 x 200 mm, 2-component grip, with non-slip grip



Your advantages

- The tools feature ergonomic two-component safety handles
- · Large contact surface of blades inside screw head

Commercial data

Item number	1212550
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BH31
Product key	BH3141
Catalog page	Page 443 (C-3-2019)
GTIN	4046356589857
Weight per piece (including packing)	47.8 g
Weight per piece (excluding packing)	47.8 g
Customs tariff number	82054000
Country of origin	CZ

SF-SL 0,6X3,5-200 - Screwdriver



https://www.phoenixcontact.com/us/products/1212550



Technical data

Notes

Output Bladed imensions Width 26 mm Blade width 3.5 mm Blade height 200 mm Length 281 mm Wrench size for mounting 0 mm Blade thickness 0.6 mm Idaterial specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	Environmental Product Compliance	
Type Screwdriver tools Type straight Connection data Output Bladed Jimensions Width 26 mm Blade width 3.5 mm Blade height 200 mm Length 281 mm Wrench size for mounting 0 mm Blade thickness 0.6 mm Idaterial specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	California Proposition 65	
Product type Screwdriver tools Type straight onnection data Output Bladed imensions Width 26 mm Blade width 3.5 mm Blade height 200 mm Length 281 mm Wrench size for mounting 0 mm Blade thickness 0.6 mm atterial specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	roduct properties	
Type straight Connection data Output Bladed Immensions Width 26 mm Blade width 3.5 mm Blade height 200 mm Length 281 mm Wrench size for mounting 0 mm Blade thickness 0.6 mm Interial specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	Туре	Bladed
Output Bladed Dimensions Width 26 mm Blade width 3.5 mm Blade height 200 mm Length 281 mm Wrench size for mounting 0 mm Blade thickness 0.6 mm Daterial specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	Product type	Screwdriver tools
Output Bladed imensions Width 26 mm Blade width 3.5 mm Blade height 200 mm Length 281 mm Wrench size for mounting 0 mm Blade thickness 0.6 mm Identical specifications Material alloyed tool steel Tests DIN/ISO 2380-1	Туре	straight
Width 26 mm Blade width 3.5 mm Blade height 200 mm Length 281 mm Wrench size for mounting 0 mm Blade thickness 0.6 mm Interial specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	Connection data	
Width 26 mm Blade width 3.5 mm Blade height 200 mm Length 281 mm Wrench size for mounting 0 mm Blade thickness 0.6 mm Interial specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	Output	Bladed
Blade width Blade height 200 mm Length 281 mm Wrench size for mounting Blade thickness 0.6 mm Material specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	Dimensions	
Blade height 200 mm Length 281 mm Wrench size for mounting 0 mm Blade thickness 0.6 mm Interial specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	Width	26 mm
Length 281 mm Wrench size for mounting 0 mm Blade thickness 0.6 mm Interial specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	Blade width	3.5 mm
Wrench size for mounting 0 mm Blade thickness 0.6 mm Interial specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	Blade height	200 mm
Blade thickness 0.6 mm Interial specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	Length	281 mm
Interial specifications Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1 Iounting	Wrench size for mounting	0 mm
Material alloyed tool steel tandards and regulations Tests DIN/ISO 2380-1	Blade thickness	0.6 mm
tandards and regulations Tests DIN/ISO 2380-1 Jounting	Material specifications	
Tests DIN/ISO 2380-1 lounting	Material	alloyed tool steel
lounting	standards and regulations	
-	Tests	DIN/ISO 2380-1
-	Mounting	
	•	0 mm

SF-SL 0,6X3,5-200 - Screwdriver



https://www.phoenixcontact.com/us/products/1212550



Classifications

ECLASS

	ECLASS-11.0	21040407		
	ECLASS-12.0	21040407		
	ECLASS-13.0	21040407		
ETIM				
	ETIM 9.0	EC000158		
UNSPSC				
	UNSPSC 21.0	27111700		

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com