CRIMPFOX 2,5-M - Crimping pliers

1212719

https://www.phoenixcontact.com/us/products/1212719

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm² ... 2.5 mm², lateral entry, trapezoidal crimp

Your advantages

- Unlockable pressure lock
- · Marked die stations for precise processing of corresponding cross sections
- · All ferrules can be optimally crimped with a minimum amount of effort even in the case of large conductor cross sections
- · Consistently high crimping quality

Commercial data

| Item number | 1212719 |
|--------------------------------------|---------------------|
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BH31 |
| Product key | BH3131 |
| Catalog page | Page 416 (C-3-2019) |
| GTIN | 4046356857789 |
| Weight per piece (including packing) | 624.3 g |
| Weight per piece (excluding packing) | 624.3 g |
| Customs tariff number | 82032000 |
| Country of origin | SE |

CRIMPFOX 2,5-M - Crimping pliers

1212719

https://www.phoenixcontact.com/us/products/1212719



Technical data

Notes

| California Proposition 65 | Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration |
|---------------------------|------------------------------------------------------------------------------------------------------------------|
| duct properties | |
| Product type | Crimping tool |
| Compression | Trapezoidal crimp |
| Crimping position 1 | |
| Min. cross section | 0.5 mm ² |
| Max. cross section | 1.5 mm ² |
| AWG min | 20 |
| AWG max | 16 |
| Crimping position 2 | |
| Max. cross section | 2.5 mm ² |
| AWG max | 14 |
| Crimping position 3 | |
| Max. cross section | 0.25 mm² |
| AWG max | 24 |

Connection data

Conductor connection

| Cross section range, metric | 0.25 mm ² 2.5 mm ² |
|-----------------------------|------------------------------------------|
| Cross section range AWG | 24 14 |

Dimensions

| Width | 22 mm |
|--------|--------|
| Height | 76 mm |
| Length | 204 mm |

Material specifications

| Color | black |
|-------|-------|
| | |

CRIMPFOX 2,5-M - Crimping pliers

1212719

https://www.phoenixcontact.com/us/products/1212719



Classifications

ECLASS

| ECLASS-11.0 | 21043811 |
|-------------|----------|
| ECLASS-12.0 | 21043811 |
| ECLASS-13.0 | 21043811 |

ETIM

| | ETIM 9.0 | EC000168 | |
|----|-------------|----------|--|
| UN | UNSPSC | | |
| | UNSPSC 21.0 | 27111500 | |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com