

# SI-FP-R1A-U1A-D1A - Front plate

1404497

<https://www.phoenixcontact.com/us/products/1404497>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Front plate with contact inserts, plastic with shroud, 1 x RJ45, 8-pos. metal, CAT5e (socket/socket); 1 x USB (socket/socket) type A; 1 x 9-pos. D-SUB (socket/socket)

## Commercial data

Item number	1404497
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF70
Product key	BF7EDX
Catalog page	Page 710 (C-2-2019)
GTIN	4046356698405
Weight per piece (including packing)	76 g
Weight per piece (excluding packing)	75.8 g
Customs tariff number	85366990
Country of origin	CZ

# SI-FP-R1A-U1A-D1A - Front plate

1404497

<https://www.phoenixcontact.com/us/products/1404497>

## Technical data

### Notes

General	Strain relief USB internal: cable tie
---------	---------------------------------------

### Product properties

Product type	Data front plate
Number of slots	3
Shielded	yes


### Electrical properties

Rated voltage (III/3)	max. 48 V AC/DC (D-SUB 9, USB A)
	max. 42.4 V DC (D-SUB 9, USB A, RJ45, UL rating)
	max. 30 V AC (D-SUB 9, USB A, RJ45, UL rating)
Rated current	3 A (D-SUB 9)
	1.5 A (USB A)
	max. 175 mA (RJ45, UL rating)

### Connection data

Tightening torque	0.8 ... 1 Nm
-------------------	--------------

### Dimensions

Dimensional drawing	
Width	50.7 mm
Height	87.5 mm
Depth	60 mm

### Material specifications

Material Front plate	PBT
----------------------	-----

### Connector

Contact insert design	with 1x D-SUB 9 Socket/socket, slot locking UNC 4...40 bolts
	with 1x RJ45 Socket/socket, snap-in slot locking
	with 1x USB A 3.0 Socket/socket, snap-in slot locking

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP20
----------------------	------

# SI-FP-R1A-U1A-D1A - Front plate



1404497

<https://www.phoenixcontact.com/us/products/1404497>

Ambient temperature (operation)	-10 °C ... 60 °C
---------------------------------	------------------

## Mounting

Assembly instructions	suitable for all mounting frames
-----------------------	----------------------------------

# SI-FP-R1A-U1A-D1A - Front plate



1404497

<https://www.phoenixcontact.com/us/products/1404497>

## Classifications

### ECLASS

ECLASS-11.0	27182806
ECLASS-12.0	27182806
ECLASS-13.0	27182806

### ETIM

ETIM 9.0	EC000456
----------	----------

### UNSPSC

UNSPSC 21.0	39121300
-------------	----------

# SI-FP-R1A-U1A-D1A - Front plate



1404497

<https://www.phoenixcontact.com/us/products/1404497>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)