

EV-T2SF - Panel mounting frames



1405218

<https://www.phoenixcontact.com/us/products/1405218>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CHARX connect basic, Panel mounting frames, Accessories, for attaching to infrastructure charging sockets, Type 2, IEC 62196-2, Front mounting, M5 thread, housing: black, Without logo

Product description

Panel mounting frame for Socket Outlet

Your advantages

- Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- Individual branding, thanks to the use your own logo

Commercial data

| | |
|--------------------------------------|--------------------|
| Item number | 1405218 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | EM01 |
| Product key | XWBAFC |
| Catalog page | Page 46 (C-7-2019) |
| GTIN | 4046356738514 |
| Weight per piece (including packing) | 58.4 g |
| Weight per piece (excluding packing) | 58 g |
| Customs tariff number | 39269097 |
| Country of origin | DE |

EV-T2SF - Panel mounting frames



1405218


<https://www.phoenixcontact.com/us/products/1405218>

Technical data

Product properties

| | |
|-------------------|--|
| Product type | Panel mounting frame for Socket Outlet |
| Product family | CHARX connect basic |
| Application | for attaching to infrastructure charging sockets |
| Type | Accessories |
| Affixed logo | Without logo |
| Charging standard | Type 2 |
| Charging mode | Mode 3, Case B |

Dimensions

| | |
|---------------------|--|
| Width | 76.6 mm |
| Height | 76.8 mm |
| Depth | 13.4 mm |
| Dimensional drawing |  |
| Bore dimensions | 60 mm x 60 mm |

Material specifications

| | |
|--------------------|--------------|
| Color (Housing) | black (9005) |
| Material (Housing) | Plastic |

Environmental and real-life conditions

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -30 °C ... 50 °C |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |

Standards and regulations

Standards

| | |
|-----------------------|-------------|
| Standards/regulations | IEC 62196-2 |
|-----------------------|-------------|

Mounting

| | |
|--------------------------------|--|
| Mounting type Protective cover | Front mounting (rear screw connection) |
| Fixing screws | M5 thread |

EV-T2SF - Panel mounting frames



1405218

<https://www.phoenixcontact.com/us/products/1405218>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27144792 |
| ECLASS-12.0 | 27144792 |
| ECLASS-13.0 | 27144792 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002884 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121500 |
|-------------|----------|

EV-T2SF - Panel mounting frames



1405218
<https://www.phoenixcontact.com/us/products/1405218>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com