

1406409

https://www.phoenixcontact.com/us/products/1406409

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact carrier, Universal, 4-position, Socket, straight, M12, coding: S, PCB mounting, THR solder connection, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0. 1%) item no.: 1238743

Your advantages

- · For compact devices: transmit high power in a confined space
- · Reduced mounting costs thanks to two-piece device connector
- · All common pin assignments and codings available
- Easy device integration thanks to mechanical port screw connections with threaded attachment, press-in contour or direct integration in the front plate
- · Packaging available for automated pick and place assembly

Commercial data

Item number	1406409
Packing unit	20 pc
Minimum order quantity	20 pc
Sales key	AB23
Product key	ABQAGU
Catalog page	Page 288 (C-2-2013)
GTIN	4046356804349
Weight per piece (including packing)	4.5 g
Weight per piece (excluding packing)	4.195 g
Customs tariff number	85366990
Country of origin	DE



1406409

https://www.phoenixcontact.com/us/products/1406409

Technical data

Notes

General	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the
	connector must be sealed using a protective cap > IP54.
	Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Product properties

Product type	Contact insert
Sensor type	Universal
Number of positions	4
Application	Power
Seal present	no
Shielded	no
Coding	S
Thread type	M12

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	6 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U _N	630 V
Nominal current I _N	12 A

Connection data

Connection method	THR solder connection
-------------------	-----------------------

Interfaces

Signal type/category	Universal

Material specifications

Flammability rating according to UL 94	V0
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 4T

Connector

Connection 1



1406409

https://www.phoenixcontact.com/us/products/1406409

Packaging specifications

Type of packaging

Head design	Socket
Head cable outlet	straight
Head thread type	M12
Coding	S
Cable/line	
Signal type/category	Universal
Mechanical properties Mechanical data	
Insertion/withdrawal cycles	> 100
Ambient conditions	
Degree of protection (when plugged in)	IP67 (correctly plugged in and locked)
Degree of protection	IP67 (correctly plugged in and locked)
	IP67, when plugged in
Ambient temperature (operation)	-25 °C 105 °C
	-40 °C 105 °C (without mechanical actuation)
Standards and regulations	
M12	
Standard designation	M12 connector
Mounting	
Mounting type	PCB mounting

Blister



1406409

https://www.phoenixcontact.com/us/products/1406409

Classifications

UNSPSC 21.0

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27460201
ETIM	
ETIM 9.0	EC002635
UNSPSC	

39121400



1406409

https://www.phoenixcontact.com/us/products/1406409

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com